Rieber

M E T A cooking

Top-Selection



We are **more than cooking**

We are **digital & sustainable**

We are **META cooking**

more
about us

Dispenser

Program Overview





Stainless steel tube dispenser unheated - for round dishes

Unheated roundware stacker, with 1 or 2 tubes Ø 397mm (max. load 75 kg), flexibly adjustable by 3 adjustment rods for roundware Ø 190-320mm, stacking height approx. 600mm. Dispensing height adjustable via springs. With platform, safety push handle, 4 bumper corners, rustproof castors (2 swivel & 2 swivel stop castors).



Stainless steel tube dispenser heated - for round/square dishes

Statically heated stacker for dishes: round/square, +30°C to +110°C. With polycarbonate lid, double-walled insulated, with 1 / 2 tubes Ø 397mm (round dishes max. Ø 190-320 mm), flexibly adjustable by 3 adjustment rods, max. stacking height approx. 600mm. With platform, safety push handle, 4 bumper corners, stainless castors (2 swivel & 2 swivel stop castors). Rated voltage 1N AC 230 V 50 Hz.



Stainless steel tube dispenser convection heated - for round dishes

Circulating air heated roundware stacker, +30°C to +110°C. With polycarbonate lid, double-walled insulation, with 1 / 2 tubes Ø 397mm, flexibly adjustable by 3 adjustment rods. For round dishes Ø 190-320mm, max. stacking height approx. 600mm. With platform, safety push handle, 4 bumper corners, stainless castors (2 swivel & 2 swivel stop castors). Rated voltage 1N AC 230 V 50 Hz.



Stainless steel tube dispenser unheated for installation - for square dishes


Statically heated tube ø 397mm (max. load 75 kg), flexibly adjustable by 3 adjustment rods for round dishes ø 190-320mm, stacking height approx. 600mm. Dispensing height adjustable via springs.

Digital HACCP documentation - safe & time-saving

Digital HACCP documentation with our CHECK HACCP system. Hygiene, cleaning & maintenance checklists via app, can be used anywhere. Paper & complete HACCP, can be viewed centrally in your dashboard in real time from anywhere.



Checklists QR code - can be retrofitted at any time - Order No. 94 01 01 14



Stainless steel tube dispenser heated for installation - for round dishes

Statically heated round utensil installation tube, tubes Ø 397mm, flexibly adjustable by 3 adjustment rods for round utensils Ø 190-320mm (max. load 75 kg). Dispensing height adjustable via springs. With polycarbonate lid, anti-tilt & anti-tilt platform, for an installation depth of 685mm. Rated voltage 1N AC 230 V 50 Hz.



Stainless steel exchange dispenser unheated - for universal dishes

Unheated universal harness stacker (max. load 150 or 200 kg) with grid platform (36 holes), tilt- and tilt-proof. Spring force adjustable according to harness weight, safety push handle, 4 bumper corners, stainless steel castors (2 swivel & 2 swivel stop castors).



Stainless steel interchangeable dispenser heated - for universal dishes

Statically heated universal dish stacker +30°C to +110°C (max. load 150 or 200 kg). With polycarbonate lid, double-walled insulation, with grid platform (36 holes). Spring force adjustable according to harness weight, 6 interchangeable bars, safety push handle, 4 bumper corners, stainless steel castors (2 swivel & 2 swivel stop castors). Rated voltage 1N AC 230 V 50 Hz.



Stainless steel interchangeable dispenser convection heated - for universal dishes

Circulating air heated universal dish stacker +30°C to +110°C (max. load 150 or 200 kg). Double-walled insulated, adjustable spring force, safety push handle, stainless steel castors (2 swivel & 2 swivel stop castors). Also available in shortened length for flush fitting in niches. Rated voltage 1N AC 230 V 50 Hz.

Dispenser

Program Overview






Platform dispenser open stainless steel unheated - for GN & EN trays & baskets

Suitable for baskets and trays (GN & EN, with dimensions 530x400 or 800mm), stacking height approx. 575mm. Platform guided tilt- & tilt-proof, max. load 200 kg. Spring force flexibly adjustable, with safety push handle, 4 bumper corners, stainless steel castors (2 swivel & 2 swivel stop castors).



Platform dispenser open stainless steel unheated - for baskets

Suitable for baskets (with dimension 500x500mm), stacking height approx. 575mm. Platform guided tilt- & tilt-proof, max. load 200 kg. Spring force flexibly adjustable, with safety push handle, 4 bumper corners, stainless steel castors (2 swivel & 2 swivel stop castors).



Platform dispenser open stainless steel heated - for installation - for baskets

Suitable for baskets, platform guided against tipping & tilting, spring force flexibly adjustable, with rectangular support frame, for an installation depth of 580 or 740mm.



Platform dispenser open stainless steel unheated - for installation for baskets & trays

Suitable for baskets and GN trays Platform guided tilt- & tilt-proof, spring force flexibly adjustable, with rectangular egg-bearing frame, for an installation depth of 580 or 740mm.

Digital HACCP documentation - safe & time-saving

Digital HACCP documentation with our CHECK HACCP system. Hygiene, cleaning & maintenance checklists via app, can be used anywhere. Paper & complete HACCP, can be viewed centrally in your dashboard in real time from anywhere.



Checklists QR code - can be retrofitted at any time - Order No. 94 01 01 14



Platform dispenser closed unheated - for baskets & JVA menu trays

Suitable for baskets, stacking height approx. 600mm. Double-walled insulated. With support frame, platform guided tilt- & tilt-proof, max. load 200 kg. Spring force flexibly adjustable, with safety push handle, 4 bumper corners, rustproof castors (2 swivel & 2 swivel stop castors).



Platform dispenser closed unheated - for plastic parts

Suitable for plastic parts, with slotted hole insert, stacking height approx. 600mm. Double-walled insulated. With support frame, platform guided tilt- & tilt-proof, max. load 200 kg. Spring force flexibly adjustable, with safety push handle, 4 bumper corners, rustproof castors (2 swivel & 2 swivel stop castors).



Platform dispenser closed convection-cooled - for baskets

For baskets (with max. dimension 500x500mm) +5°C to +8°C, with attached stainless steel lid 68mm, stacking height approx. 600mm. Double-walled insulated. With support frame, platform tilt- & tilt-proof, max. load 200 kg. Spring force flexibly adjustable, with safety push handle, 4 bumper corners, stainless steel castors (2 swivel & 2 swivel stop castors). Refrigerant R134a, nominal voltage 1N AC 230 V 50 Hz.



Platform dispenser closed convection heated - for GN trays & JVA menu trays

Only for stainless steel GN baskets (with dimension max. 530x650mm), with stainless steel lid 35mm can be hooked in at the front, stacking height approx. 600mm. Double-walled insulated. With support frame, platform guided tilt- & tilt-proof, max. load 200 kg. Spring force flexibly adjustable, with safety push handle, 4 bumper corners, stainless steel castors (2 swivel & 2 swivel stop castors). Rated voltage 1N AC 230 V 50 Hz.

Dispenser

Program Overview





Platform dispenser closed convection heated - for GN- & EN trays

Only for stainless steel baskets GN & EN (with dimension max. 530x800mm), with stainless steel lid 35mm can be hooked in at the front, stacking height approx. 600mm. Double-walled insulated. With support frame, platform tilt- & tilt-proof, max. load 200 kg. Spring force flexibly adjustable, with safety push handle, 4 bumper corners, stainless steel castors (2 swivel & 2 swivel stop castors). Rated voltage 1N AC 230 V 50 Hz.



Platform dispenser closed convection heated - for baskets

Only for stainless steel baskets (with dimension max. 500x500mm), with stainless steel lid 35mm can be hooked in at the front, stacking height approx. 600mm. Double-walled insulated. With support frame, platform guided tilt- & tilt-proof, max. load 200 kg. Spring force flexibly adjustable, with safety push handle, 4 bumper corners, stainless steel castors (2 swivel & 2 swivel stop castors). Rated voltage 1N AC 230 V 50 Hz.



Ultra dispenser made of stainless steel convection heated - for heat & ultrasonic bowls

2 tubes for 92 ultrasonic bowls (Ø255), stacking height 610mm, shaft dia. 260x260mm per tube. Max. load 75kg, anti-tilt platform, flexible adjustable springs. Double-walled, reinforced heat insulation, reduced surface temperature. 2 stainless steel hinged lids, safety push handle, 4 bumper corners, stainless steel castors (2 swivel & 2 swivel stop castors). Rated voltage 1N AC 230 V 50 Hz.

Digital HACCP documentation - safe & time-saving

Digital HACCP documentation with our CHECK HACCP system. Hygiene, cleaning & maintenance checklists via app, can be used anywhere. Paper & complete HACCP, can be viewed centrally in your dashboard in real time from anywhere.



Checklists QR code - can be retrofitted at any time - Order No. 94 01 01 14





Stainless steel tube dispenser unheated - for round dishes



Unheated roundware stacker, with 1 or 2 tubes Ø 397mm (max. load 75 kg), flexibly adjustable by 3 adjustment rods for roundware Ø 190-320mm, stacking height approx. 600mm. Dispensing height adjustable via springs. With platform, safety push handle, 4 bumper corners, rustproof castors (2 swivel & 2 swivel stop castors).

More info



Tubular dispenser 1x - unheated

Number of tubes: 1 | Castor Ø 125 mm | Incl. cover hood: Not included

Dimensions mm	Weight kg	Order no.
620 x 480 x 900	21,5	89010468



Tubular dispenser 2x - unheated

Number of tubes: 2 | Castor Ø 125 mm | Incl. cover hood: Not included

Dimensions mm	Weight kg	Order no.
955 x 480 x 900	32,5	89010469



Tubular dispenser 2x - with slits

Number of tubes: 2 | Castor Ø 125 mm | Incl. cover hood: Not included

Dimensions mm	Weight kg	Order no.
955 x 480 x 900	31,0	89010369



Built-in disp. ERRV-190-320-750 - 2010

Stacking height: 600 mm | {number of tubes: 1 | Incl. lid cover: Not included

Dimensions mm	Weight kg	Order no.
750	6,0	89050350



Built-in disp. ERRV-190-320-640 - 2010

Stacking height: 495 mm | {number of tubes: 1 | Incl. lid cover: Not included

Dimensions mm	Weight kg	Order no.
640	5,7	89050351

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

Stainless steel tube dispenser heated - for round/square dishes



Statically heated stacker for dishes: round/square, +30°C to +110°C. With polycarbonate lid, double-walled insulated, with 1 / 2 tubes Ø 397mm (round dishes max. Ø 190-320 mm), flexibly adjustable by 3 adjustment rods, max. stacking height approx. 600mm. With platform, safety push handle, 4 bumper corners, stainless castors (2 swivel & 2 swivel stop castors). Rated voltage 1N AC 230 V 50 Hz.

More info

Tubular dispenser RRV-H1 190-320 - 2010

Number of tubes: 1 | Protection class: IPX5 | Castor Ø 125 mm | Incl. cover hood: Included (1x in plastic)



Dimensions mm	Weight kg	Connected load W	Order no.
618 x 480 x 1030	32,5	866	89010268

Tubular dispenser RRV-H2 190-320 - 2010

Number of tubes: 2 | Protection class: IPX5 | Castor Ø 125 mm | Incl. cover hood: Included (2x in plastic)



Dimensions mm	Weight kg	Connected load W	Order no.
955 x 480 x 1030	47,0	1.400	89010269

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

Stainless steel tube dispenser convection heated - for round dishes

Circulating air heated roundware stacker, +30°C to +110°C. With polycarbonate lid, double-walled insulation, with 1 / 2 tubes Ø 397mm, flexibly adjustable by 3 adjustment rods. For round dishes Ø 190-320mm, max. stacking height approx. 600mm. With platform, safety push handle, 4 bumper corners, stainless castors (2 swivel & 2 swivel stop castors). Rated voltage 1N AC 230 V 50 Hz.

More info





Tubular dispenser RRV-U1 190-320

Number of tubes: 1 | Protection class: IPX5 | Castor Ø 125 mm | Incl. cover hood: Included (1x in plastic)

Dimensions mm	Weight kg	Connected load W	Order no.
620 x 480 x 1030	33,8	900	89010168



Tubular dispenser RRV-U2 190-320

Number of tubes: 2 | Protection class: IPX5 | Castor Ø 125 mm | Incl. cover hood: Included (2x in plastic)

Dimensions mm	Weight kg	Connected load W	Order no.
986 x 480 x 1030	49,0	1.460	89010169

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

Stainless steel tube dispenser unheated for installation - for square dishes

Statically heated tube ø 397mm (max. load 75 kg), flexibly adjustable by 3 adjustment rods for round dishes ø 190-320mm, stacking height approx. 600mm. Dispensing height adjustable via springs.

More info



Multipurpose pipe EWE 590x290-750 ,2005

Stack height: 540 mm | Shaft dimensions i. L.: 590 x 290 mm



Dimensions mm	Weight kg	Order no.
674 x 334 x 745,8	11,0	59034903

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

Stainless steel tube dispenser heated for installation - for round dishes



Statically heated round utensil installation tube, tubes Ø 397mm, flexibly adjustable by 3 adjustment rods for round utensils Ø 190-320mm (max. load 75 kg). Dispensing height adjustable via springs. With polycarbonate lid, anti-tilt & anti-tilt platform, for an installation depth of 685mm. Rated voltage 1N AC 230 V 50 Hz.

More info



Built-in disp. ERRV-H-190-320-685 - 2010

Stacking height: 495 mm | {number of tubes: 1 | Protection class: IPX4 | Incl. cover hood: Included (1x in plastic) | Cover cutout: 380 mm | Cutout for switch cover: 152 x 85 mm

Tube diameter mm	Weight kg	Connected load W	Order no.
397	14,0	550	89050425



Built-in disp. ERRV-H-190-320-785 - 2010

Stacking height: 600 mm | {number of tubes: 1 | Protection class: IPX4 | Incl. cover hood: Included (1x in plastic) | Cover cutout: 380 mm | Cutout for switch cover: 152 x 85 mm

Tube diameter mm	Weight kg	Connected load W	Order no.
397	14,5	550	89050426

Built-in disp. ERRV-H-190-280-685 - 2005

Stacking height: 595 mm | {number of tubes: 1 | Protection class: IPX4 | Incl. cover hood: Included (1x in plastic) | Cover cutout: 380 mm | Cutout for switch cover: 152 x 85 mm

Tube diameter mm	Weight kg	Connected load W	Order no.
372	14,3	550	89050423

Built-in disp. ERRV-H-190-280-785 - 2005

Stacking height: 700 mm | {number of tubes: 1 | Protection class: IPX4 | Incl. cover hood: Included (1x in plastic) | Cover cutout: 380 mm | Cutout for switch cover: 152 x 85 mm

Tube diameter mm	Weight kg	Connected load W	Order no.
372	15,0	550	89050424

Made in Germany

Tube dispenser accessories

Matching accessories for the tube dispenser - such as matching stainless steel lid for optimal insulation or a poly lid cover, as well as bracket.

More info

Lid s/s - ERR-325/RR/RRH/RRU

Matching flat, double-walled, insulated stainless steel lid, lockable, for all round tubular dispenser models, as an alternative to the standard plastic lid.



Weight kg	Order no.
1,3	89060102

Hood poly - RRV/ERRV 190-320

Matching plastic lid hood, 130 mm high, for round tubular dispensers.

Weight kg	Order no.
0,9	89060115

Hood poly - for RRV/ERRV 190-280

Weight kg	Order no.
0,7	89060109

Lid holder - for tubular dispenser

Lid holder for a 130 mm polycarbonate lid for tubular dispensers.

Weight kg	Order no.
-	89061001

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

Stainless steel exchange dispenser unheated - for universal dishes

Unheated universal harness stacker (max. load 150 or 200 kg) with grid platform (36 holes), tilt- and tilt-proof. Spring force adjustable according to harness weight, safety push handle, 4 bumper corners, stainless steel castors (2 swivel & 2 swivel stop castors).

More info





Exchange dispenser - unheated

Shaft dimensions i. L.: 590 x 290 mm | Stacking height without/with cover: 560 mm / 645 mm | Castor Ø 125 mm | Incl. lid hood: Not included | Platform type: Grid platform with 6 guide bars

Dimensions mm	Weight kg	Order no.
955 x 480 x 900	37,5	89010459



Exchange dispenser - unheated Q 1/1

Shaft dimensions i. L.: 525 x 590 mm | Stacking height without/with cover: 600 mm | Castor Ø 125 mm | Incl. lid hood: Not included | Platform type: 36-hole platform with 6 guide bars

Dimensions mm	Weight kg	Order no.
750 x 690 x 911	49,5	89020212

Made in Germany

Stainless steel interchangeable dispenser heated - for universal dishes



Statically heated universal dish stacker +30°C to +110°C (max. load 150 or 200 kg). With polycarbonate lid, double-walled insulation, with grid platform (36 holes). Spring force adjustable according to harness weight, 6 interchangeable bars, safety push handle, 4 bumper corners, stainless steel castors (2 swivel & 2 swivel stop castors). Rated voltage 1N AC 230 V 50 Hz.

More info

Exchange dispenser - WE-H - 2005



Shaft dimensions i. L.: 590 x 290 mm | Stacking height without/with cover hood: 560 mm / 645 mm | Protection class: IPX5 | Castor Ø 125 mm | Incl. lid hood: Included (1x in plastic) | Platform type: Grid platform

Dimensions mm	Weight kg	Connected load W	Order no.
955 x 480 x 1030	53,0	1.700	89010259

Exchange dispenser - WE-H - 750 - 2005



Shaft dimensions i. L.: 590 x 290 mm | Stacking height without/with cover hood: 560 mm / 645 mm | Protection class: IPX5 | Castor Ø 125 mm | Incl. lid hood: Included (1x in plastic) | Platform type: Grid platform

Dimensions mm	Weight kg	Connected load W	Order no.
750 x 420 x 1030	50,5	1.700	89010260

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

Stainless steel interchangeable dispenser convection heated - for universal dishes

Circulating air heated universal dish stacker +30°C to +110°C (max. load 150 or 200 kg). Double-walled insulated, adjustable spring force, safety push handle, stainless steel castors (2 swivel & 2 swivel stop castors). Also available in shortened length for flush fitting in niches. Rated voltage 1N AC 230 V 50 Hz.

More info





Exchange dispenser - WE-U

Shaft dimensions i. L.: 590 x 290 mm | Stacking height without/with cover hood: 545 mm / 645 mm | Protection class: IPX5 | Castor Ø 125 mm | Incl. lid hood: Included (1x in plastic) | Platform type: Grid platform with 6 guide bars

Dimensions mm	Weight kg	Connected load W	Order no.
955 x 480 x 1030	55,2	1.800	89010159



Exchange dispenser - WE-QU1/1

Shaft dimensions i. L.: 525 x 590 mm | Stacking height without/with cover hood: 600 mm | Protection class: IPX5 | Castor Ø 125 mm | Incl. lid hood: Included (1 x in stainless steel) | Platform type: 36-hole platform with 6 guide bars

Dimensions mm	Weight kg	Connected load W	Order no.
860 x 690 x 911	67,0	2.250	89020108

Made in Germany

Exchange dispenser accessories

Matching accessories for the exchange dispenser - such as corresponding matching stainless steel cover hood for optimal insulation.

More info

Hood s/s - WE-H,WE-U,WE-L,WE

Matching stainless steel lid hood, 70 mm high, for all exchange dispenser models (except Q models).

Weight kg	Order no.
2,6	89060110

Hood s/s 1/1 - 30mm - PG/WE-Q1/1

Stainless steel lid hood 1/1, low, 30 mm high, suitable for Q 1/1 platform and exchange dispenser baskets.

Weight kg	Order no.
4,0	89070101

Hood poly - WE-H,WE-U,WE-L,WE

Matching plastic lid hood, 130 mm high, for unheated exchange dispensers.

Weight kg	Order no.
1,1	89060112

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

Platform dispenser open stainless steel unheated - for GN & EN trays & baskets



Suitable for baskets and trays (GN & EN, with dimensions 530x400 or 800mm), stacking height approx. 575mm. Platform guided tilt- & tilt-proof, max. load 200 kg. Spring force flexibly adjustable, with safety push handle, 4 bumper corners, stainless steel castors (2 swivel & 2 swivel stop castors).

More info



Platform dispenser open - SV 1/1

Platform dimensions: 412 x 545 mm | Basket/Tray Dimensions: max. 530 x 400 mm | stacking height: 575 mm | castor Ø 125 mm | Basket capacity: 6 x (530 x 400 x 85 mm) oder 4 x (530 x 400 x 120 mm)

Dimensions mm	Weight kg	Order no.
690 x 690 x 911	35,0	89020301



Platform dispenser open - SV 2/1

Platform dimensions: 812 x 545 mm | Basket/Tray Dimensions: max. 530 x 800 mm | stacking height: 575 mm | castor Ø 125 mm | Basket capacity: 12 x (530 x 400 x 85 mm) oder 8 x (530 x 400 x 120 mm) oder 6 x (530 x 800 x 85 mm) oder 4 x (530 x 800 x 120 mm)

Dimensions mm	Weight kg	Order no.
1050 x 690 x 911	43,0	89020302



Platform dispenser open - GN 2/1

Platform dimensions: 662 x 545 mm | Basket/Tray Dimensions: max. 530 x 650 mm | stacking height: 575 mm | castor Ø 125 mm | Basket capacity: 7 x (530 x 650 x 75 mm) oder 5 x (530 x 650 x 115 mm) oder 10 x (530 x 325 x 115 mm)

Dimensions mm	Weight kg	Order no.
880 x 690 x 911	39,0	89020303



Platform dispenser open - trays 1/1

Platform dimensions: 535 x 412 mm | Basket/Tray Dimensions: max. 530 x 400 mm | stacking height: 575 mm | castor Ø 125 mm | Basket capacity: 6 x (530 x 400 x 85 mm) oder 4 x (530 x 400 x 120 mm)

Dimensions mm	Weight kg	Order no.
680 x 500 x 911	28,5	89020306

Made in Germany

Platform dispenser open stainless steel unheated - for baskets

Suitable for baskets (with dimension 500x500mm), stacking height approx. 575mm. Platform guided tilt- & tilt-proof, max. load 200 kg. Spring force flexibly adjustable, with safety push handle, 4 bumper corners, stainless steel castors (2 swivel & 2 swivel stop castors).

More info



Platform dispenser open - Q 1/1

Platform dimensions: 537 x 555 mm | Basket/Tray Dimensions: max. 500 x 500 mm | stacking height: 575 mm | castor Ø 125 mm | Basket capacity: 7 x (500 x 500 x 75 mm) oder 5 x (500 x 500 x 115 mm) oder 8 x (500 x 500 x 70 mm) oder 5 x (500 x 500 x 70 mm mit Geschirrkorb-aufsatz)




Dimensions mm	Weight kg	Order no.
690 x 690 x 911	36,0	89020304

Made in Germany


Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

Platform dispenser open stainless steel heated - for installation - for baskets

Suitable for baskets, platform guided against tipping & tilting, spring force flexibly adjustable, with rectangular support frame, for an installation depth of 580 or 740mm.




More info



Built-in platform disp. EPU-Q1/1, H=600

Installation depth: 600 mm or stacking height: 430 mm | Platform dimensions: 535 x 535 mm | Basket/Tray dimensions: max. 530 x 530 mm | Switch panel cutout: 176 x 108 mm | Incl. lid cover: Included (1 x in stainless steel) | Finish: square

Dimensions mm	Weight kg	Connected load W	Order no.
717 x 736 x 700	51,0	1.560	89030301



Built-in platform disp. EPU-Q1/1, H=760

Installation depth: 760 mm or stacking height: 640 mm | Platform dimensions: 535 x 535 mm | Basket/Tray dimensions: max. 530 x 530 mm | Switch panel cutout: 176 x 108 mm | Incl. lid cover: Included (1 x in stainless steel) | Finish: square

Dimensions mm	Weight kg	Connected load W	Order no.
705 x 664 x 760	60,0	1.560	89030302

Made in Germany

Platform dispenser open stainless steel unheated - for installation for baskets & trays

Suitable for baskets and GN trays Platform guided tilt- & tilt-proof, spring force flexibly adjustable, with rectangular egg-bearing frame, for an installation depth of 580 or 740mm.

More info



Built-in platform disp. EPO-Q1/1 H=580

Platform dimensions: 535 x 535 mm | Basket/Tray Dimensions: max. 530 x 530 mm | stacking height: 430 mm | finish:



Dimensions mm	Weight kg	Order no.
666 x 628 x 580	16,0	89030101

Built-in platform disp. EPO-Q1/1, H=750

Platform dimensions: 535 x 535 mm | Basket/Tray Dimensions: max. 530 x 530 mm | stacking height: 590 mm | finish:



Dimensions mm	Weight kg	Order no.
666 x 628 x 740	19,0	89030102

Built-in platform disp. EPO-GN1/1 H=580

Platform dimensions: 535 x 385 mm | Basket/Tray Dimensions: max. 530 x 370 mm | stacking height: 455 mm | finish:



Dimensions mm	Weight kg	Order no.
666 x 478 x 580	13,5	89030103

Built-in platform disp. EPO-GN1/1 H=750

Platform dimensions: 535 x 385 mm | Basket/Tray Dimensions: max. 530 x 370 mm | stacking height: 590 mm | finish:



Dimensions mm	Weight kg	Order no.
666 x 478 x 750	16,0	89030104

Built-in platform disp. EPG-Q1/1, H=580

Platform dimensions: 535 x 535 mm | Basket/Tray Dimensions: max. 530 x 530 mm | stacking height: 430 mm | finish: square



Dimensions mm	Weight kg	Order no.
666 x 628 x 580	21,0	89030201

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.



Built-in platform disp. EPG-Q1/1, H=750

Platform dimensions: 535 x 535 mm | Basket/Tray Dimensions: max. 530 x 530 mm | stacking height: 590 mm | finish: square

Dimensions	Weight	Order no.
mm	kg	
666 x 628 x 750	24,5	89030202

Made in Germany

Platform dispenser closed unheated - for baskets & JVA menu trays

Suitable for baskets, stacking height approx. 600mm. Double-walled insulated. With support frame, platform guided tilt- & tilt-proof, max. load 200 kg. Spring force flexibly adjustable, with safety push handle, 4 bumper corners, rustproof castors (2 swivel & 2 swivel stop castors).

More info



Platform dispenser - unheated 630x425

Platform dimensions: | Basket/Tray Dimensions: | Castor Ø 125 mm | Basket capacity:



Dimensions mm	Weight kg	Order no.
871 x 580 x 911	46,2	89020214

Platform dispenser - PG-GN2/1

Platform dimensions: 535 x 660 mm | Basket/Tray Dimensions: max. 530 x 650 mm | Castor Ø 125 mm | Basket capacity: 8 x (530 x 650 x 75 mm) oder 5 x (530 x 650 x 115 mm)



Dimensions mm	Weight kg	Order no.
880 x 690 x 911	50,0	89020201

Platform dispenser - unheated SV 2/1

Platform dimensions: 535 x 810 mm | Basket/Tray Dimensions: max. 530 x 800 mm | Castor Ø 125 mm | Basket capacity: 14 x (530 x 400 x 85 mm) oder 10 x (530 x 400 x 120 mm) oder 7 x (530 x 800 x 85 mm) oder 5 x (530 x 800 x 120 mm)



Dimensions mm	Weight kg	Order no.
1040 x 690 x 911	54,5	89020206

Platform dispenser - unheated Q 1/1

Platform dimensions: 535 x 505 mm | Basket/Tray Dimensions: max. 500 x 500 mm | Castor Ø 125 mm | Basket capacity: 8 x (500 x 500 x 115 mm) oder 5 x (500 x 500 x 115 mm) oder 8 x (500 x 500 x 70 mm) oder 5 x (500 x 500 x 70 mm mit Geschirrkorbaufsatz)



Dimensions mm	Weight kg	Order no.
730 x 690 x 911	46,2	89020202

Platform disp. PG-GN 2x1/1, cutlery box

Platform dimensions: 535 x 330 mm | Basket/Tray Dimensions: 530 x 325 mm | Castor Ø 125 mm | Basket capacity:



Dimensions mm	Weight kg	Order no.
960 x 690 x 1340	80,0	89020215

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

Platform dispenser closed unheated - for plastic parts



Suitable for plastic parts, with slotted hole insert, stacking height approx. 600mm. Double-walled insulated. With support frame, platform guided tilt- & tilt-proof, max. load 200 kg. Spring force flexibly adjustable, with safety push handle, 4 bumper corners, rustproof castors (2 swivel & 2 swivel stop castors).

More info

Platform dispenser - PG-4S

Platform dimensions: 566 x 566 mm | Castor Ø 125 mm

Dimensions mm	Weight kg	Order no.
790 x 690 x 911	56,0	89020203



Platform dispenser - PG-6S

Platform dimensions: 587 x 566 mm | Castor Ø 125 mm

Dimensions mm	Weight kg	Order no.
1090 x 690 x 911	61,0	89020204

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

Platform dispenser closed convection-cooled - for baskets



For baskets (with max. dimension 500x500mm) +5°C to +8°C, with attached stainless steel lid 68mm, stacking height approx. 600mm. Double-walled insulated. With support frame, platform tilt- & tilt-proof, max. load 200 kg. Spring force flexibly adjustable, with safety push handle, 4 bumper corners, stainless steel castors (2 swivel & 2 swivel stop castors). Refrigerant R134a, nominal voltage 1N AC 230 V 50 Hz.

More info

platform disp. PK-Q1/1 refrigerated R290

Platform dimensions: 535 x 505 mm | Basket/Tray Dimensions: max. 500 x 500 mm | Castor Ø 125 mm



Dimensions mm	Weight kg	Connected load W	Order no.
1161 x 812 x 950	140,0	410	89020402

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

Platform dispenser closed convection heated - for GN trays & JVA menu trays



Only for stainless steel GN baskets (with dimension max. 530x650mm), with stainless steel lid 35mm can be hooked in at the front, stacking height approx. 600mm. Double-walled insulated. With support frame, platform guided tilt- & tilt-proof, max. load 200 kg. Spring force flexibly adjustable, with safety push handle, 4 bumper corners, stainless steel castors (2 swivel & 2 swivel stop castors). Rated voltage 1N AC 230 V 50 Hz.

More info



Platform dispenser - PU-630x425 85°

Heating range: +30°C to +85°C | Platform dimensions: | Basket/Tray Dimensions: | Castor Ø 125 mm | finish: square

Dimensions mm	Weight kg	Connected load W	Order no.
994 x 647 x 960	69,0	2.400	89020125



Platform dispenser - PU-630x425 140°

Heating range: +30°C to +140°C | Platform dimensions: | Basket/Tray Dimensions: | Castor Ø 125 mm | finish: square

Dimensions mm	Weight kg	Connected load W	Order no.
994 x 647 x 960	69,0	2.400	89020124



Platform dispenser - PU-GN2/1

Heating range: +30°C to +100°C | Platform dimensions: 535 x 660 mm | Basket/Tray Dimensions: max. 530 x 650 mm | Castor Ø 125 mm | finish:

Dimensions mm	Weight kg	Connected load W	Order no.
990 x 690 x 911	70,2	2.240	89020103



Menu tray dispenser - PU-M2/1

Heating range: +50°C to +185°C | Platform dimensions: 535 x 660 mm | Basket/Tray Dimensions: max. 530 x 650 mm | Castor Ø 125 mm | finish:

Dimensions mm	Weight kg	Connected load W	Order no.
1148 x 744 x 911	90,0	2.250	89020107

Made in Germany

Platform dispenser closed convection heated - for GN- & EN trays

Only for stainless steel baskets GN & EN (with dimension max. 530x800mm), with stainless steel lid 35mm can be hooked in at the front, stacking height approx. 600mm. Double-walled insulated. With support frame, platform tilt- & tilt-proof, max. load 200 kg. Spring force flexibly adjustable, with safety push handle, 4 bumper corners, stainless steel castors (2 swivel & 2 swivel stop castors). Rated voltage 1N AC 230 V 50 Hz.

More info



Platform dispenser - PU-SV2/1

Heating range: +30°C to +100°C | Platform dimensions: 535 x 810 mm | Basket/Tray Dimensions: max. 530 x 800 mm | Castor Ø 125 mm | finish:



Dimensions mm	Weight kg	Connected load W	Order no.
1142 x 690 x 911	77,2	2.240	89020102

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

Platform dispenser closed convection heated - for baskets



Only for stainless steel baskets (with dimension max. 500x500mm), with stainless steel lid 35mm can be hooked in at the front, stacking height approx. 600mm. Double-walled insulated. With support frame, platform guided tilt- & tilt-proof, max. load 200 kg. Spring force flexibly adjustable, with safety push handle, 4 bumper corners, stainless steel castors (2 swivel & 2 swivel stop castors). Rated voltage 1N AC 230 V 50 Hz.

More info



Platform dispenser - PU-Q1/1

Heating range: +30°C to +100°C | Platform dimensions: 535 x 510 mm | Basket/Tray Dimensions: max. 500 x 500 mm | Castor Ø 125 mm | finish: square

Dimensions mm	Weight kg	Connected load W	Order no.
840 x 690 x 911	64,0	2.240	89020104

Made in Germany

Platform dispenser Accessories

Matching accessories for the platform dispensers - such as matching stainless steel lid hoods for optimum insulation, perforated insert trays, various stainless steel/plastic baskets or a practical cutlery attachment.

More info

Hood s/s, tall plastic crockery PG-6S

Stainless steel lid hood, low, 35 mm high, suitable for platform dispensers with large plastic insulated crockery.

Weight kg	Order no.
-	89070401

Hood s/s, low, plastic crockery -PG-4S

Stainless steel lid hood, low, 35 mm high, suitable for platform dispensers with small plastic insulated crockery.

Weight kg	Order no.
-	89070301

Hood s/s 1/1 - 30mm - PG/WE-Q1/1

Stainless steel lid hood 1/1, low, 30 mm high, suitable for Q 1/1 platform and exchange dispenser baskets.

Weight kg	Order no.
4,0	89070101

Hood s/s 2/1 - 30mm - PG-GN2/1

Stainless steel lid hood 2/1, low, 30 mm high, suitable for GN 2/1 platform dispensers.



Weight kg	Order no.
3,0	89070201

Basket rilsan coat.SV 2/1-530x800x120mm

Basket made of rilsan-coated steel wire, grey heat-resistant plastic coating, with corner reinforcement (40x25 mm mesh size, 2.5 mm wire mesh diameter, 6 mm stacking frame diameter) - suitable for EN and GN 2/1 platform dispensers.

Weight kg	Order no.
3,4	89060204

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

Basket rilsan coat.SV 2/1 - 530x800x85mm

Basket made of rilsan-coated steel wire, grey heat-resistant plastic coating, with corner reinforcement (40x25 mm mesh size, 2.5 mm wire mesh diameter, 6 mm stacking frame diameter) - suitable for EN and GN 2/1 platform dispensers.

Weight kg	Order no.
3,2	89060203

Basket rilsan coat.GN 2/1-530x650x115mm

Basket made of rilsan-coated steel wire, grey heat-resistant plastic coating, with corner reinforcement (40x25 mm mesh size, 2.5 mm wire mesh diameter, 6 mm stacking frame diameter) - suitable for GN 2/1 platform dispensers.

Weight kg	Order no.
2,0	89060206

Basket rilsan coat.GN 2/1 - 530x650x75mm

Basket made of rilsan-coated steel wire, grey heat-resistant plastic coating, with corner reinforcement (40x25 mm mesh size, 2.5 mm wire mesh diameter, 6 mm stacking frame diameter) - suitable for GN 2/1 platform dispensers.

Weight kg	Order no.
2,0	89060205

Basket rilsan coat.Q 1/1 - 500x500x115mm

Basket made of rilsan-coated steel wire, grey heat-resistant plastic coating, with corner reinforcement (40x25 mm mesh size, 2.5 mm wire mesh diameter, 6 mm stacking frame diameter) - suitable for Q 1/1 platform dispenser baskets.

Weight kg	Order no.
2,2	89060208

Basket rilsan coat.Q 1/1 - 500x500x75mm

Basket made of rilsan-coated steel wire, grey heat-resistant plastic coating, with corner reinforcement (40x25 mm mesh size, 2.5 mm wire mesh diameter, 6 mm stacking frame diameter) - suitable for Q 1/1 platform dispenser baskets.

Weight kg	Order no.
1,5	89060207

Basket CNS SV 2/1 - 530x800x120mm

Basket made of stainless steel wire, with corner reinforcement (40x25 mm mesh size, 2.5 mm wire mesh diameter, 6 mm stacking frame diameter) - suitable for EN and GN 2/1 platform dispensers.

Weight kg	Order no.
1,7	89060304

Basket CNS SV 2/1 - 530x800x85mm

Basket made of stainless steel wire, with corner reinforcement (40x25 mm mesh size, 2.5 mm wire mesh diameter, 6 mm stacking frame diameter) - suitable for EN and GN 2/1 platform dispensers.

Weight kg	Order no.
1,4	89060303

Basket CNS GN 2/1 - 530x650x115mm

Basket made of stainless steel wire, with corner reinforcement (40x25 mm mesh size, 2.5 mm wire mesh diameter, 6 mm stacking frame diameter) - suitable for GN 2/1 platform dispensers.

Weight kg	Order no.
2,3	89060306

Basket CNS GN 2/1 - 530x650x75mm

Basket made of stainless steel wire, with corner reinforcement (40x25 mm mesh size, 2.5 mm wire mesh diameter, 6 mm stacking frame diameter) - suitable for GN 2/1 platform dispensers.

Weight kg	Order no.
2,2	89060305

Basket CNS Q 1/1 - 500x500x115mm

Basket made of stainless steel wire, with corner reinforcement (40x25 mm mesh size, 2.5 mm wire mesh diameter, 6 mm stacking frame diameter) - suitable for Q 1/1 platform dispenser baskets.

Weight kg	Order no.
2,0	89060308

Basket CNS SV 1/1 - 530x400x120mm

Basket made of stainless steel wire, with corner reinforcement (40x25 mm mesh size, 2.5 mm wire mesh diameter, 6 mm stacking frame diameter) - suitable for EN and GN 1/1 platform dispensers.

Weight kg	Order no.
1,5	89060302

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

Basket CNS Q 1/1 - 500x500x75mm

Basket made of stainless steel wire, with corner reinforcement (40x25 mm mesh size, 2.5 mm wire mesh diameter, 6 mm stacking frame diameter) - suitable for Q 1/1 platform dispenser baskets.

Weight kg	Order no.
1,7	89060307

Basket CNS SV 1/1 - 530x400x85mm

Basket made of stainless steel wire, with corner reinforcement (40x25 mm mesh size, 2.5 mm wire mesh diameter, 6 mm stacking frame diameter) - suitable for EN and GN 1/1 platform dispensers.

Weight kg	Order no.
1,4	89060301

Basket, plastic Q 1/1 - close meshed

Plastic basket, narrow mesh with corner reinforcement - suitable for Q 1/1 platform dispenser baskets (only for use with refrigerated/neutral dispensers - not heated dispensers).

Weight kg	Order no.
1,8	89060401

Basket, plastic Q 1/1 - wide meshed

Plastic basket, wide mesh with corner reinforcement - suitable for Q 1/1 platform dispenser baskets (only for use with refrigerated/neutral dispensers - not heated dispensers).

Weight kg	Order no.
2,1	89060404

Cutlery gantry 4x - for platf. dispenser

Cutlery gantry, 4-part, for open platform dispensers.

Weight kg	Order no.
7,0	89060903

Sheet, perf. - platf.dispenser SV2/1

Stainless steel metal sheet, perforated, for all SV 2/1 platform dispensers.

Weight kg	Order no.
6,5	89071004

Sheet, perf. - platf.dispenser GN2/1

Stainless steel metal sheet, perforated, for all GN 2/1 platform dispensers.

Weight kg	Order no.
5,1	89071002

Sheet, perf. - platf.dispenser Q1/1

Stainless steel metal sheet, perforated, for all Q 1/1 platform dispensers.

Weight kg	Order no.
2,9	89071001

GN tray - granite decor 530x325mm

GN-Gastronorm tray, granite decor colour, 530x325 mm - for use with all GN tray trolley models.

Weight kg	Order no.
0,2	89080281

Ultra dispenser made of stainless steel convection heated - for heat & ultrasonic bowls



2 tubes for 92 ultrasonic bowls (Ø255), stacking height 610mm, shaft dia. 260x260mm per tube. Max. load 75kg, anti-tilt platform, flexible adjustable springs. Double-walled, reinforced heat insulation, reduced surface temperature. 2 stainless steel hinged lids, safety push handle, 4 bumper corners, stainless steel castors (2 swivel & 2 swivel stop castors). Rated voltage 1N AC 230 V 50 Hz.

More info



Ultra dispenser ERE-260 - 2014

Number of tubes: 2 | Protection class: IPX5 | Castor Ø 125 mm | Incl. cover hood: Included (2 x in stainless steel)

Dimensions mm	Weight kg	Connected load W	Order no.
1005 x 508 x 1011	75,0	3.200	89040104



Ultra dispenser WEU-Ultra

Number of tubes: 1 für 30 Speiseschalen | Protection class: IPX5 | Castor Ø 125 mm | Incl. cover hood: Included (1 x in stainless steel)

Dimensions mm	Weight kg	Connected load W	Order no.
1005 x 508 x 1011	70,0	3.200	89040105

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

Ultra dispenser accessories

Suitable accessories for the Ultra stackers - such as the matching ultrasonic bowls made of stainless steel, also with aluminium core, various safe gloves for handling without risk of burns.

More info

Ultra bowl CNS - Ø255mm

Ultra bowl made of stainless steel, double-walled, with a wax filling, 255 mm diameter.



Weight kg	Order no.
0,8	89080141

Heat storage bowl s/s - Ø255mm alu core

Weight kg	Order no.
0,7	89080130

Gloves - for Ultra bowls

Gloves for use with Ultra bowls (5-fingered).

Weight kg	Order no.
0,1	89061201

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.