Rieber

M E T A cooking

Top-Selection



We are **more than cooking**

We are **digital & sustainable**

We are **META cooking**

more
about us

delivery trolley - ZUB heated - with warming tubs



Stainless steel ladle trolley with deep-drawn, seamlessly welded-in GN 1/1 warming tray at the top, can be heated wet & dry (significant energy savings when dry), with drain tap, separately adjustable from +30°C to 110°C. Cover embodied on all sides, handle on front/longitudinal side, insulated on all sides, stainless steel shelf welded in at bottom with 4 butt corners, stainless steel castors. Rated voltage 1N AC 230V 50Hz.

More info



ZUB 1 well

Capacity: 1 x GN 1/1, 200 mm | Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 2.500 mm | Protection type: IPX4 | Splashproof | 2 fixed-; 2 swivel castors with brakes | Castor Ø: 125 mm | 4 corner bumpers

Dimensions mm	Weight kg	Connected load W	Push handle	Order no.
715 x 475 x 900	22,9	470	short side	88160101



ZUB 2 wells

Capacity: 2 x GN 1/1, 200 mm | Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 2.500 mm | Protection type: IPX4 | Splashproof | 2 fixed-; 2 swivel castors with brakes | Castor Ø: 125 mm | 4 corner bumpers

Dimensions mm	Weight kg	Connected load W	Push handle	Order no.
816 x 677 x 900	33,2	940	short side	88160201
816 x 677 x 900	33,2	940	long side	88160203



ZUB 3 wells

Capacity: 3 x GN 1/1, 200 mm | Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 2.500 mm | Protection type: IPX4 | Splashproof | 2 fixed-; 2 swivel castors with brakes | Castor Ø: 125 mm | 4 corner bumpers

Dimensions mm	Weight kg	Connected load W	Push handle	Order no.
1185 x 678 x 900	44,2	1.410	short side	88160301
1185 x 678 x 900	44,2	1.410	long side	88160303



ZUB 4 wells

Capacity: 4 x GN 1/1, 200 mm | Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 2.500 mm | Protection type: IPX4 | Splashproof | 2 fixed-; 2 swivel castors with brakes | Castor Ø: 125 mm | 4 corner bumpers

Dimensions mm	Weight kg	Connected load W	Push handle	Order no.
1520 x 678 x 900	54,9	1.880	short side	88160401
1520 x 717 x 900	56,9	3.060	long side	88160403

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

delivery trolley - ZUB cooled - with cooling tubs



Stainless steel ladle trolley with deep-drawn, seamlessly welded-in GN 1/1 cooling trays at the top, cooling machine adjustable from +2°C to 10°C below. Cover embodied on all sides, safety push handle at front, insulated on all sides, with drain cock, welded-in stainless steel shelf with 4 butt corners at bottom, stainless steel castors. VT -10°C, rated voltage 1N AC 230V 50Hz.

More info

ZUB 2-wells - refrigerated R290



Capacity: 2 x GN 1/1, 200 mm | Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 2.500 mm | Protection type: IPX0 | Splashproof | 2 fixed-; 2 swivel castors with brakes | Castor Ø: 125 mm | 4 corner bumpers

Dimensions mm	Weight kg	Connected load W	Refrigerant	Order no.
854 x 665 x 900	55,0	265	R290	88160804

ZUB 3-wells - refrigerated R290



Capacity: 3 x GN 1/1, 200 mm | Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 2.500 mm | Protection type: IPX0 | Splashproof | 2 fixed-; 2 swivel castors with brakes | Castor Ø: 125 mm | 4 corner bumpers

Dimensions mm	Weight kg	Connected load W	Refrigerant	Order no.
1190 x 665 x 900	62,0	265	R290	88160805

ZUB 4 wells - refrigerated R290



Capacity: 4 x GN 1/1, 200 mm | Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 2.500 mm | Protection type: IPX0 | Splashproof | 2 fixed-; 2 swivel castors with brakes | Castor Ø: 125 mm | 4 corner bumpers

Dimensions mm	Weight kg	Connected load W	Refrigerant	Order no.
1507 x 665 x 900	75,0	265	R290	88160806

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

delivery trolley - ZUB heated - with warming tubs for daycare & schools



Stainless steel ladle trolley, child-friendly working height of 750 mm, deep-drawn, seamlessly welded GN 1/1 warming tray at the top, can be heated wet & dry (significant energy savings when dry) with drain tap, separately adjustable +30 to 110 °C, insulated on all sides. Top incl. sneeze guard & light, cover cranked on all sides, handle on front side, 2x shelf on long side, closed cabinet space with 4 butt corners, rustproof castors. Rated voltage 1N AC 230V 50 Hz.

More info



Children buffet trolley 2-h=750 / 800 mm

Capacity: 2 x GN 1/1, 200 mm | Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 2.500 mm | Protection type: | Splashproof | 2 fixed-; 2 swivel castors with brakes | Castor Ø: 100 mm | 4 corner bumpers

Dimensions mm	Weight kg	Connected load W	Push handle	Order no.
818 x 679 x 1150	49,8	940	short side	88160212



Children buffet trolley 3-h=750 / 800 mm

Capacity: 3 x GN 1/1, 200 mm | Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 2.500 mm | Protection type: | Splashproof | 2 fixed-; 2 swivel castors with brakes | Castor Ø: 100 mm | 4 corner bumpers

Dimensions mm	Weight kg	Connected load W	Push handle	Order no.
1187 x 679 x 1150	63,5	1.420	short side	88160312



Children buffet trolley 4- h=750 / 800 m

Capacity: 4 x GN 1/1, 200 mm | Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 2.500 mm | Protection type: | Splashproof | 2 fixed-; 2 swivel castors with brakes | Castor Ø: 100 mm | 4 corner bumpers

Dimensions mm	Weight kg	Connected load W	Push handle	Order no.
1522 x 679 x 1150	78,0	1.900	short side	88160412

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

Delivery trolley accessories

Matching accessories for the ZUB feeder trolleys - such as various attachment variants & combinations of light and/or thermal bridges. Fold-down shelf variants (longitudinal/frontal), as well as practical drain screens for the trays.

More info

Gantry light/heat - ZUB 4

Matching gantry with a lighting/thermal bridge for all ZUB and Bain Marie 4 models - with a germ guard on the guest side, adjustable in 4 ways.



Weight kg	Order no.
15,0	88161002

Gantry light/heat - Norm trolley & ZUB 3

Matching gantry with a lighting/thermal bridge for all STW and ZUB 3 models, without a sliding/hinged lid.



Weight kg	Order no.
15,5	88132048

Gantry light..- ZUB/bain-marie 4

Matching gantry with a lighting bridge for all ZUB and Bain Marie 4 models - with a germ guard on the guest side, adjustable in 4 ways.



Weight kg	Order no.
15,0	88161001

Gantry light/heat, Norm trolley & ZUB 2

Matching gantry with a lighting/thermal bridge for all STW and ZUB 2 models, without a sliding/hinged lid.



Weight kg	Order no.
8,0	88132046

Gantry light - Norm trolley & ZUB 3

Matching gantry with a lighting bridge for all STW and ZUB 3 models, without a sliding/hinged lid.



Weight kg	Order no.
13,5	88132047

Made in Germany

Gantry light - Norm trolley & ZUB 2

Matching gantry with a lighting bridge for all STW and ZUB 2 models, without a sliding/hinged lid.



Weight kg	Order no.
8,0	88132045

HING.SHELF F.LONG SIDE OF ZUB 4



Weight kg	Order no.
5,0	58161704

HING.SHELF F.LONG SIDE OF ZUB 3



Weight kg	Order no.
3,0	58161703

HING.SHELF COMPL.F.LONG SIDE OF ZUB 2



Weight kg	Order no.
3,0	58161702

HING.SHELF COMPL. F.NARROW SIDE OF ZUB 3



Weight kg	Order no.
2,0	58161701

HING.SHELF COMPL.F.ZUB 1,2,3,4 PARTS



Weight kg	Order no.
1,2	58162401

basket strainer in s/s for drainpipe

Weight kg	Order no.
0,0	57010301

Food transport trolley - STW with cabinet compartment heated - without warming trays

Stainless steel serving trolley with smooth top cover and all-round gallery. Bottom 2 or 3 heated GN 1/1 compartments in H3 (IPX5), separately adjustable +30°C to 110°C, 14 deep-drawn bead pairs each. Doors double-walled insulated & self-closing, transport lock. Safety push handle at front, 2 fixed & 2 swivel castors with double stops. Rated voltage 1N AC 230V 50/60Hz.

More info



Trolley Norm II-0, heated

Connector type: Safety switch (type F) | Cable type: spiral cable | Cable length: 2.000 mm | Protection type: IPX4 | Jet-proof | 2 fixed-; 2 swivel castors | Castor Ø: 125 mm | 4 corner bumpers



Dimensions mm	Weight kg	Connected load W	Order no.
905 x 680 x 900	55,0	940	88130323

Trolley Norm II-2, heated

Connector type: Safety switch (type F) | Cable type: spiral cable | Cable length: 2.000 mm | Protection type: IPX4 | Jet-proof | 2 fixed-; 2 swivel castors | Castor Ø: 125 mm | 4 corner bumpers



Dimensions mm	Weight kg	Connected load W	Order no.
905 x 680 x 900	60,0	1.880	88130623

Trolley Norm III - 0, heated

Connector type: Safety switch (type F) | Cable type: spiral cable | Cable length: 2.000 mm | Protection type: IPX4 | Jet-proof | 2 fixed-; 2 swivel castors | Castor Ø: 125 mm | 4 corner bumpers



Dimensions mm	Weight kg	Connected load W	Order no.
1314 x 680 x 900	81,7	1.410	88131023

Trolley Norm III - 3, heated

Connector type: Safety switch (type F) | Cable type: spiral cable | Cable length: 2.000 mm | Protection type: IPX4 | Jet-proof | 2 fixed-; 2 swivel castors | Castor Ø: 125 mm | 4 corner bumpers



Dimensions mm	Weight kg	Connected load W	Order no.
1314 x 680 x 900	84,7	2.820	88131423

Made in Germany

Food transport trolley - STW with cabinet compartment 1xheated, 1xcooled & warming trays

Top 3 deep-drawn GN 1/1 warming trays wet & dry heatable. Bottom 1xheated & 1xcooled GN 1/1 cabinet compartment in H3 (IPX5). Hot: +30°C to 90°C, cold: +2°C to +10°C, 8 deep-drawn bead pairs each. Doors double-walled insulated, self-closing, transport lock. Safety push handle at front, 2 fixed & 2 swivel castors with double stops. Rated voltage 1N AC 230V 50/60Hz.

More info





Trolley Norm III-1-1K heat., refrig.R290

Connector type: Safety switch (type F) | Cable type: spiral cable | Cable length: 2.000 mm | Protection type: IPX4 | Splashproof | 2 fixed-; 2 swivel castors | Castor Ø: 125 mm | 4 corner bumpers

Dimensions mm	Weight kg	Connected load W	Refrigerant	Order no.
1314 x 680 x 900	89,7	2.820	R290	88131825

Made in Germany

STW Accessories

Suitable accessories for the STW food transport trolleys, such as various top versions & combinations of light and/or thermal bridges. Appropriate folding or sliding lid options, an extension with coupling & drawbar or additional fold-down footprint, as well as digital thermometers or practical drainage sieves for the tubs. Up to GN cooling or heating pellets for additional passive cold / hot holding for sliding onto the support ledges in the cabinet space below. Can also be equipped with all-round impact protection for perfect protection.

More info

Gantry light/heat, Norm trolley & ZUB 2

Matching gantry with a lighting/thermal bridge for all STW and ZUB 2 models, without a sliding/hinged lid.



Weight kg	Order no.
8,0	88132046

Gantry light/heat - Norm trolley & ZUB 3

Matching gantry with a lighting/thermal bridge for all STW and ZUB 3 models, without a sliding/hinged lid.



Weight kg	Order no.
15,5	88132048

Gantry light - Norm trolley & ZUB 2

Matching gantry with a lighting bridge for all STW and ZUB 2 models, without a sliding/hinged lid.



Weight kg	Order no.
8,0	88132045

Gantry light - Norm trolley & ZUB 3

Matching gantry with a lighting bridge for all STW and ZUB 3 models, without a sliding/hinged lid.



Weight kg	Order no.
13,5	88132047

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

GN cooling pellet CNS 1/1 - 30mm

Stainless steel GN 1/1 cooling plate for pre-heating and passive cooling during the transportation of food in Rieber thermoport® models, can be inserted horizontally on the support rails.



Weight	Order no.
kg	
5,6	85012002

GN cooling pellet plastic 1/1 - orange

Plastic GN 1/1 cooling plate for pre-heating and passive cooling during the transportation of food in Rieber thermoport® models, can be inserted horizontally on the support rails.



Weight	Order no.
kg	
2,6	85022038

Hinged lid - Norm trolley 2

Extra hinged lid for all STW 2 models - 1/3 on the guest side and 2/3 at the back.



Weight	Order no.
kg	
14,0	88132071

Hinged lid - Norm trolley 3

Extra hinged lid for all STW 3 models - 1/3 on the guest side and 2/3 at the back.



Weight	Order no.
kg	
-	88132072

Drawbar/coupl. - Norm trolley 2-comp.

Drawbar and coupling system suitable for 2-comp. STW models - for transporting with tractor units.



Weight	Order no.
kg	
-	88221105

Drawbar/coupl. - Norm trolley 3-comp.

Drawbar and coupling system suitable for 3-comp. STW models - for transporting with tractor units.



Weight	Order no.
kg	
-	88221106

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

Sliding cover, pull-out - Norm trolley 2


Extra sliding lid for all STW 2 models - insulated, can be pulled out over the face sides, 100 mm locking position, not retrofittable.



Weight kg	Order no.
20,0	88132069

Sliding cover, pull-out - Norm trolley 3

Extra sliding lid for all STW 3 models - insulated, can be pulled out over the face sides, 100 mm locking position, not retrofittable.



Weight kg	Order no.
25,0	88132070

Storage surface CNS hinged - front

Hinged storage surface made of stainless steel on the face side for all STW models - for storing plates and similar items.



Weight kg	Order no.
2,0	88132002

All-round bumper - Norm trolley 2

Extra all-round impact protection for all STW 2 models.



Weight kg	Order no.
-	88132065

All-round bumper - Norm trolley 3

Extra all-round impact protection for all STW 3 models.



Weight kg	Order no.
-	88132066

basket strainer in s/s for drainpipe

Weight kg	Order no.
0,0	57010301

Longlife Digital Thermometer 0 - 120°C



Weight kg	Order no.
0,0	33070402