Rieber

M E T A cooking

Top-Selection



We are **more than cooking**

We are **digital & sustainable**

We are **META cooking**

more
about us

thermoport® Premium stainless steel

Program Overview





thermoport® stainless steel Top loader portable - heated

Heated food transport box with insulated lid, self-regulating silicone foil heating fix +86°C max. +95°C, only wet heatable. Hygienic double-walled & tightly welded. For stacking GN containers/thermoplates® with watertight plug-in lids, for reliable & insulated food transport. All thermoport® models can be stacked in combination with each other. Rated voltage 1N AC 230V 50/60Hz.


Can be used directly as a scoop dispenser via the removable thermoport® lid. Transport & dispensing in one. Max. Capacity with GN: Size 100: 26L



thermoport® stainless steel Front loader mobile - unheated

Unheated food transport trolleys with insulated door, interior hygienic design H3. Hygienic double-walled & tightly welded. For insertion of GN containers/thermoplates® with watertight plug-in lid, for reliable & insulated food transport. All thermoport® models, plastic & stainless steel are stackable in combination. Optimally mobile with 2 fixed & 1 swivel stop castors, safely protected by 4 bumper corners.

Safe cold & hot holding with matching GN cooling/heating pellets. Max. Capacity with GN: Size 1000: 38L | 1400: 63.7L | 1600: 70.4L | 2000: 89.7L | 3000: 130L



thermoport® stainless steel Front loader mobile - convection heated

Circulating air heated food transport box with insulated door, digitally adjustable circulating air heating max. +100°C. Interior hygienic design H3. Hygienic double-walled & tightly welded. For insertion of GN containers/thermoplates® with watertight plug-in lid. All thermoport® plastic & stainless steel can be stacked together. Rated voltage 1N AC 230V 50/60Hz. Optimally mobile with 2 fixed & 1 swivel stop castors, safely protected by 4 bumper corners.

Precise to the degree, powerful digital convection heating, up to max. +100 °C. Max. Capacity with GN: Size 1000: 38L | 1400: 63.7L | 1600: 70.4L | 2000: 89.7L | 3000: 130L



hybrid kitchen - models 140 °C with lid | 200 °C thermoport® canteen

The special hybrid door with separately digitally controllable heaters & fans, max. 140°C. Functional programmes: Cold & hot holding simultaneously/separately, regeneration, cooking, with individually adjustable time, humidification, setpoint chamber/core temperature. Removable lid, with stacking embossing & seal. Interior H2 tightly welded, jointless support beads. Rated voltage 1N AC 230V 50Hz. Optimum mobility with 2 fixed & 1 swivel castors, safely protected by 4 bumper corners.

Auto prog. function can be stored for a 100% guarantee of success. Usable w/o high volt. curr. (230V), structural measures, extractor hood, water connections, etc.

Digital HACCP documentation - safe & time-saving

Digital documentation with our CHECK HACCP system. Automatic room temperature recording in the thermoport®, via retrofittable sensors. Paper- & seamless HACCP during transport, in real time, viewable from anywhere in your dashboard.



Automatic room temp. sensor - can be retrofitted any time - order no. 94020138



thermoport® stainless steel Front loader portable - unheated

Unheated food transport box with insulated door, interior hygienic design H3. Hygienic double-walled & tightly welded. For inserting GN containers/thermoplates® with watertight plug-in lid, for reliable & insulated food transport. All thermoport® models, plastic & stainless steel are stackable in combination.

Max. Capacity with GN: Size 1000: 38L



thermoport® stainless steel Front loader portable - convection heated

Circulating-air heated food transport box with insulated door, digitally adjustable circulating-air heating max. +90°C. Interior hygienic design H3. Hygienic double-walled & tightly welded. For inserting GN containers/thermoplates® with watertight plug-in lid. All thermoport® plastic & stainless steel can be stacked together. Rated voltage 1N AC 230V 50/60Hz.

Max. Capacity with GN: Size 1000: 38L



thermoport® stainless steel Front loader mobile - cooled

Refrigerated food transport trolley with insulated door and digitally controllable refrigerating machine, interior hygienic design H3. Double-walled & tightly welded. For inserting GN containers/thermoplates® with watertight plug-in lid. Thermoport® plastic & stainless steel can be stacked together. Rated voltage 1N AC 230V 50/60Hz. Optimum mobility with 2 fixed & 1 swivel castors, safely protected by 4 bumper corners.

Hygienic, as cooling meanders in the side walls, no germs in the interior. Max. Capacity with GN: Size 1000: 38L | 1600: 70.4L | 2000: 89.7L | 3000: 130L



thermoport® stainless steel Front loader mobile - hybrid

Hybrid food transport trolley with 2 insulated compartments, digital convection heating at the top, cooling compartment (active/passive) at the bottom. Interior hygienic design H3. Hygienic double-walled & tightly welded. For inserting GN containers/thermoplates® with watertight plug-in lid. Thermoport® plastic & stainless steel can be stacked together. Rated voltage 1N AC 230V 50/60Hz. Optimum mobility with 2 fixed & 1 swivel castors, safely protected by 4 bumper corners.

Auto prog. function can be stored for a 100% guarantee of success. Usable w/o high volt. curr. (230V), structural measures, extractor hood, water connections, etc.

thermoport® stainless steel
Top loader portable - heated



Heated food transport box with insulated lid, self-regulating silicone foil heating fix +86°C max. +95°C, only wet heatable. Hygienic double-walled & tightly welded. For stacking GN containers/thermoplates® with watertight plug-in lids, for reliable & insulated food transport. All thermoport® models can be stacked in combination with each other. Rated voltage 1N AC 230V 50/60Hz.

More info



thermoport® CNS 105 heated

Connected load: 500 W | Plug type: Safety switch (type F) | Cable type: plain cable | Cable length: 200 mm | Ambient temperature: -20°C to +100°C

Dimensions mm	Capacity max. L	Weight kg	Function	Order no.
600 x 400 x 306	26	13,2	statically heated	85010302

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

thermoport® stainless steel
Front loader mobile - unheated



Unheated food transport trolleys with insulated door, interior hygienic design H3. Hygienic double-walled & tightly welded. For insertion of GN containers/thermoplates® with watertight plug-in lid, for reliable & insulated food transport. All thermoport® models, plastic & stainless steel are stackable in combination. Optimally mobile with 2 fixed & 1 swivel stop castors, safely protected by 4 bumper corners.

More info

thermoport® CNS 1400 unheated

Jet-proof | support distance: 37 mm | ambient temperature: -20°C to +100°C | 2 fixed-; 2 swivel castors with brakes | Castor Ø: 75 mm | Max. Load capacity: 75 kg | 4 corner bumpers



Dimensions mm	Capacity max. L	Weight kg	Support rails	Order no.
492 x 769 x 793	64	33,0	14	85011101

thermoport® CNS 1600 unheated

Jet-proof | support distance: 37 mm | ambient temperature: -20°C to +100°C | 2 fixed-; 2 swivel castors | Castor Ø: 125 mm | Max. Load capacity: 150 kg | 4 corner bumpers



Dimensions mm	Capacity max. L	Weight kg	Support rails	Order no.
492 x 769 x 930	70	36,2	16	85010608

thermoport® CNS 2000 unheated

Jet-proof | support distance: 37 mm | ambient temperature: -20°C to +100°C | 2 fixed-; 2 swivel castors | Castor Ø: 125 mm | Max. Load capacity: 150 kg | 4 corner bumpers



Dimensions mm	Capacity max. L	Weight kg	Support rails	Order no.
492 x 769 x 1078	90	41,2	20	85010707

thermoport® CNS 3000 unheated

Jet-proof | support distance: 37 mm | ambient temperature: -20°C to +100°C | 2 fixed-; 2 swivel castors | Castor Ø: 125 mm | Max. Load capacity: 150 kg | 4 corner bumpers



Dimensions mm	Capacity max. L	Weight kg	Support rails	Order no.
592 x 769 x 1448	130	60,0	30	85010807

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

thermoport® stainless steel Front loader mobile - convection heated



Circulating air heated food transport box with insulated door, digitally adjustable circulating air heating max. +100°C. Interior hygienic design H3. Hygienic double-walled & tightly welded. For insertion of GN containers/ thermoplates® with watertight plug-in lid. All thermoport® plastic & stainless steel can be stacked together. Rated voltage 1N AC 230V 50/60Hz. Optimally mobile with 2 fixed & 1 swivel stop castors, safely protected by 4 bumper corners.

More info



Thermoport® CNS 1400 circ.heated

Heating range: max. +95°C | Connected load: 765 W | Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 1.500 mm | Protection class: IPX5 | Suitable for water jets (if heating element removed) | Support distance: 37 mm | Ambient temperature: -20°C to +100°C | 2 fixed-; 2 swivel castors with brakes | Castor Ø: 75 mm | Max. Load capacity: 75 kg | 4 corner bumpers

Dimensions mm	Capacity max. L	Weight kg	Support rails	Order no.
492 x 769 x 793	64	36,4	14	85011102



thermoport® CNS 1600 circulating heated

Heating range: max. +95°C | Connected load: 763 W | Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 1.500 mm | Protection class: IPX5 | Suitable for water jets (if heating element removed) | Support distance: 37 mm | Ambient temperature: -20°C to +100°C | 2 fixed-; 2 swivel castors | Castor Ø: 125 mm | Max. Load capacity: 150 kg | 4 corner bumpers

Dimensions mm	Capacity max. L	Weight kg	Support rails	Order no.
492 x 769 x 930	70	45,0	16	85010609



thermoport® CNS 1600-D circ.heated

Heating range: max. +95°C | Connected load: 763 W | Plug type: Safety switch (type F) | Cable type: plain cable | Cable length: 1.500 mm | Protection class: IPX5 | Suitable for water jets (if heating element removed) | Support distance: 37 mm | Ambient temperature: -20°C to +100°C | 2 fixed-; 2 swivel castors | Castor Ø: 125 mm | Max. Load capacity: 150 kg | 4 corner bumpers

Dimensions mm	Capacity max. L	Weight kg	Support rails	Order no.
492 x 769 x 963	78	40,4	16	85010903

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

thermoport® CNS 2000 circulating heat

Heating range: max. +95°C | Connected load: 763 W | Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 1.500 mm | Protection class: IPX5 | Suitable for water jets (if heating element removed) | Support distance: 37 mm | Ambient temperature: -20°C to +100°C | 2 fixed-; 2 swivel castors | Castor Ø: 125 mm | Max. Load capacity: 150 kg | 4 corner bumpers



Dimensions mm	Capacity max. L	Weight kg	Support rails	Order no.
492 x 769 x 1078	90	44,0	20	85010708

thermoport® CNS 3000 circulating heat

Heating range: max. +95°C | Connected load: 763 W | Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 1.500 mm | Protection class: IPX5 | Suitable for water jets (if heating element removed) | Support distance: 37 mm | Ambient temperature: -20°C to +100°C | 2 fixed-; 2 swivel castors | Castor Ø: 125 mm | Max. Load capacity: 150 kg | 4 corner bumpers



Dimensions mm	Capacity max. L	Weight kg	Support rails	Order no.
592 x 769 x 1448	130	63,0	30	85010808

Made in Germany

hybrid kitchen - models 140 °C with lid | 200 °C thermoport® canteen



The special hybrid door with separately digitally controllable heaters & fans, max. 140°C. Functional programmes: Cold & hot holding simultaneously/ separately, regeneration, cooking, with individually adjustable time, humidification, setpoint chamber/core temperature. Removable lid, with stacking embossing & seal. Interior H2 tightly welded, jointless support beads. Rated voltage 1N AC 230V 50Hz. Optimum mobility with 2 fixed & 1 swivel castors, safely protected by 4 bumper corners.

More info



hybrid kitchen 140°C-D mobile

Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 1.500 mm | Protection class: IPX4 | Support beads: 16 | Support distance: 37 mm | Ambient temperature: +5°C to +40°C

Dimensions mm	Connected load W	Weight kg	Order no.
592 x 769 x 963	3.300	55,0	85010904



hybrid kitchen 140°C built-in

Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 1.500 mm | Protection class: IPX5 | Support beads: 16 | Support distance: 37 mm | Ambient temperature: +5°C to +40°C

Dimensions mm	Connected load W	Weight kg	Order no.
584 x 715 x 745	3.300	61,0	85010906



hybrid kitchen 200°C mobile

Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 1.500 mm | Protection class: IPX4 | Support beads: 16 | Support distance: 37 mm | Ambient temperature: +5°C to +40°C

Dimensions mm	Connected load W	Weight kg	Order no.
662 x 870 x 981	3.300	67,5	85010911



hybrid kitchen 200°C built-in

Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 1.500 mm | Protection class: IPX5 | Support beads: 16 | Support distance: 37 mm | Ambient temperature: +5°C to +40°C

Dimensions mm	Connected load W	Weight kg	Order no.
594 x 834 x 810	3.500	61,0	85010912

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

thermoport® canteen

Support beads: 16 | Support distance: 37 mm | Ambient temperature: -20°C to +100°C



Dimensions mm	Connected load W	Weight kg	Order no.
592 x 788 x 959	-	44,0	85010917

thermoport® canteen (100°C)

Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 1.500 mm | Protection class: IPX5 | Support beads: 16 | Support distance: 37 mm | Ambient temperature: -20°C to +140°C



Dimensions mm	Connected load W	Weight kg	Order no.
592 x 788 x 959	763	47,1	85010918

thermoport® canteen (hybrid 140°C)

Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 1.500 mm | Protection class: IPX5 | Support beads: 16 | Support distance: 37 mm | Ambient temperature:



Dimensions mm	Connected load W	Weight kg	Order no.
592 x 788 x 959	3.300	56,8	85010919

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

thermoport® stainless steel
Front loader portable - unheated



Unheated food transport box with insulated door, interior hygienic design H3. Hygienic double-walled & tightly welded. For inserting GN containers/ thermoplates® with watertight plug-in lid, for reliable & insulated food transport. All thermoport® models, plastic & stainless steel are stackable in combination.

More info



thermoport® CNS 1000 unheated

Support distance: 36 mm | Ambient temperature: -20°C to +100°C

Dimensions mm	Capacity max. L	Weight kg	Support rails	Order no.
410 x 665 x 470	38	19,0	8	85010404

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

thermoport® stainless steel Front loader portable - convection heated



Circulating-air heated food transport box with insulated door, digitally adjustable circulating-air heating max. +90°C. Interior hygienic design H3. Hygienic double-walled & tightly welded. For inserting GN containers/ thermoplates® with watertight plug-in lid. All thermoport® plastic & stainless steel can be stacked together. Rated voltage 1N AC 230V 50/60Hz.

More info

thermoport® CNS 1000 circulating heat

Connected load: 810 W | Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 1.500 mm | Protection class: IPX5 | Support distance: 36 mm | Ambient temperature: -20°C to +100°C



Dimensions mm	Capacity max. L	Weight kg	Support rails	Order no.
410 x 655 x 470	38	23,0	8	85010405

thermoport® CNS 1000-D circulating heat

Connected load: 810 W | Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 1.500 mm | Protection class: IPX3 | Support distance: 55 mm | Ambient temperature: -20°C to +100°C



Dimensions mm	Capacity max. L	Weight kg	Support rails	Order no.
410 x 645 x 530	52	30,0	7	85010503

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

thermoport® stainless steel
Front loader mobile - cooled



Refrigerated food transport trolley with insulated door and digitally controllable refrigerating machine, interior hygienic design H3. Double-walled & tightly welded. For inserting GN containers/thermoplates® with watertight plug-in lid. Thermoport® plastic & stainless steel can be stacked together. Rated voltage 1N AC 230V 50/60Hz. Optimum mobility with 2 fixed & 1 swivel castors, safely protected by 4 bumper corners.

More info



thermoport® s/s 1000 refrigerated R290

Connected load: 250 W |Cooling range: +2°C to +10°C | Weight: 45 kg | Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 2.000 mm | Protection class: IPX3 | Hygienic design: H3 | Splashproof | Support distance: 37 mm | 4 swivel castors with brakes | Cator Ø: 75 mm | Max. Load capacity: 75 kg | 4 corner bumpers

Dimensions mm	Capacity max. L	Support rails	Refrigerant	Order no.
492 x 769 x 770	44	8	R290	85010411



thermoport® s/s 1600 refrigerated R290

Connected load: 265 W |Cooling range: +2°C to +8°C | Weight: 50 kg | Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 2.000 mm | Protection class: IPX3 | Hygienic design: H3 | Splashproof | Support distance: 37 mm | 2 fixed-; 2 swivel castors | Cator Ø: 125 mm | Max. Load capacity: 62 kg | 4 corner bumpers

Dimensions mm	Capacity max. L	Support rails	Refrigerant	Order no.
492 x 769 x 1130	70	16	R290	85010616



thermoport® s/s 2000 refrigerated R290

Connected load: 265 W |Cooling range: +2°C to +8°C | Weight: 80 kg | Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 2.000 mm | Protection class: IPX3 | Hygienic design: H3 | Splashproof | Support distance: 37 mm | 2 fixed-; 2 swivel castors | Cator Ø: 125 mm | Max. Load capacity: | 4 corner bumpers

Dimensions mm	Capacity max. L	Support rails	Refrigerant	Order no.
492 x 769 x 1276	90	20	R290	85010718



thermoport® s/s 3000 refrigerated R290

Connected load: 265 W |Cooling range: +2°C to +8°C | Weight: 100 kg | Plug type: Safety switch (type F) | Cable type: spiral cable | Cable length: 2.000 mm | Protection class: IPX3 | Hygienic design: H3 | Splashproof | Support distance: 37 mm | 2 fixed-; 2 swivel castors | Cator Ø: 125 mm | Max. Load capacity: | 4 corner bumpers

Dimensions mm	Capacity max. L	Support rails	Refrigerant	Order no.
492 x 769 x 1646	130	30	R290	85010820

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

thermoport® stainless steel Front loader mobile - hybrid



Hybrid food transport trolley with 2 insulated compartments, digital convection heating at the top, cooling compartment (active/passive) at the bottom. Interior hygienic design H3. Hygienic double-walled & tightly welded. For inserting GN containers/thermoplates® with watertight plug-in lid. Thermoport® plastic & stainless steel can be stacked together. Rated voltage 1N AC 230V 50/60Hz. Optimum mobility with 2 fixed & 1 swivel castors, safely protected by 4 bumper corners.

More info

thermoport® CNS 3000 hybrid ak-W & pa-K



Connected load: 763 W | Plug type: Safety switch (type F) | Cable type: plain cable | Cable length: 1.500 mm | Protection type: IPX4 | Hygienic design: H3 | Suitable for water jets (if heating element removed) | Support distance: 37 mm | Ambient temperature: +2°C to +100°C | 2 fixed-; 2 swivel castors | Castor Ø: 125 mm | Max. Load capacity: 150 kg | 4 corner bumpers

Dimensions mm	Capacity max. L	Weight kg	Support rails	Order no.
492 x 769 x 1448	114	66,0	16 (warm), 8 (neutral)	85010816

thermoport® 3000 hybr.hot/cold act. R290



Connected load: 834 W | Plug type: Safety switch (type F) | Cable type: plain cable | Cable length: 2.000 mm | Protection type: IPX4 | Hygienic design: H3 | Suitable for water jets (if heating element removed) | Support distance: 37 mm | Ambient temperature: +2°C to +100°C | 2 fixed-; 2 swivel castors | Castor Ø: 125 mm | Max. Load capacity: 150 kg | 4 corner bumpers

Dimensions mm	Capacity max. L	Weight kg	Support rails	Order no.
492 x 769 x 1645	114	78,0	16 (warm), 8 (cold)	85010823

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

hybrid kitchen & thermoport® canteen Accessories

Suitable accessories for all hybrid kitchen models - for safe and shock-protected transport, the transport box made of sturdy wood for retracting the hybrid kitchen or the stainless steel GN cooling or heating pellets for additional passive cold / hot holding for sliding onto the support ledges.

More info



Protective screen front thermop. canteen

Accessory set for the thermoport® canteen consisting of an acrylic glass panel with glass mounts and hinges. Easy to install at the existing fold-out shelf mounting points. For the safe serving of food.

Weight kg	Order no.
9,2	85011718



Door thermoport® canteen (100°C)

A perfect option for the thermoport® canteen is the thermoport® canteen 100°C heatable door with active circulating air heating. Suitable for actively keeping food hot. Easy to mount. Additional cooling option is possible with the insertion of GN 1/1 cooling pellets; the cold air is distributed evenly in the interior in pure circulating air mode.

Weight kg	Order no.
8,7	85011720



Door thermoport® canteen (hybrid 140°C)

A perfect option for the thermoport® canteen is the heatable thermoport® canteen Hybrid 140°C door. For mobile and fully functional regeneration/preparation, with 2 separate, digitally controllable circulating air heating systems, a choice of programs for keeping food cold and hot at the same time or separately, as well as for regenerating and cooking food. In addition, a refrigeration function through the pure circulating air program and with the insertion of GN 1/1 cooling pellets.

Weight kg	Order no.
18,8	85011721



Door thermoport® canteen (unheated)

Weight kg	Order no.
6,0	85011719

Made in Germany

GN cooling pellet CNS 1/1 - 12,5mm

Stainless steel GN 1/1 cooling plate for pre-heating and passive cooling during the transportation of food in Rieber thermoport® models, can be inserted horizontally on the support rails.

Weight kg	Order no.
3,2	85012015

GN cooling pellet CNS 1/1 - 30mm

Stainless steel GN 1/1 cooling plate for pre-heating and passive cooling during the transportation of food in Rieber thermoport® models, can be inserted horizontally on the support rails.



Weight kg	Order no.
5,6	85012002

Transport-Box - hybrid kitchen



Weight kg	Order no.
63,0	85011717

Made in Germany

thermoport® stainless steel Accessories

Matching accessories for all thermoport® stainless steel models - such as slide-in frames for various smaller GN container sizes, stainless steel GN cooling or heating pellets for passive cold / warm holding, up to the transport protection with all-round gallery so that further thermoport® models can be stacked without slipping or the chassis for portable stainless steel thermoport® models. Can also be extended with all-round impact protection for robust protection.

More info



Insert frame - 1/6, 1/9

Stainless steel GN 1/1 insert frame with 2 cross supports - for the insertion of smaller GN sizes, such as 6x 1/6 or 9x 1/9.

Weight kg	Order no.
0,7	85012010



Insert frame - 1/4, 1/6, 2/4

Stainless steel GN 1/1 insert frame with 1 longitudinal supports - for the insertion of smaller GN sizes, such as 4x 1/4, 6x 1/6 or 2x 2/4.

Weight kg	Order no.
0,5	85012009

Sub-frame - thermoport® stainless steel

Stainless steel mobile frame with 4 corner bumpers, 2 swivel castors with brakes and 2 fixed castors for the transport of portable plastic thermoport® models.

Weight kg	Order no.
7,7	88140107

gallery with locking device



Weight kg	Order no.
1,8	85100202

All-round bumper - thermoport®3000

Weight kg	Order no.
2,3	85012054

Made in Germany

All-round bumper - TH 1400, 1600, 2000

Weight	Order no.
kg	
2,2	85012055

Transp.secur.device - thermoport® CNS

LKW-Transport securing device for mounting on all stainless steel thermoport® models - for the slip-resistant transport of stacked thermoports.



Weight	Order no.
kg	
-	85012053

GN cooling pellet CNS 1/1 - 30mm

Stainless steel GN 1/1 cooling plate for pre-heating and passive cooling during the transportation of food in Rieber thermoport® models, can be inserted horizontally on the support rails.



Weight	Order no.
kg	
5,6	85012002

GN cooling pellet CNS 1/1 - 12,5mm

Stainless steel GN 1/1 cooling plate for pre-heating and passive cooling during the transportation of food in Rieber thermoport® models, can be inserted horizontally on the support rails.

Weight	Order no.
kg	
3,2	85012015

Heating pellet CNS GN 1/1

The stainless steel heating plate {514} for pre-tempering and passive keeping warm via the food transport in Rieber thermoport® models can be inserted horizontally via the support ledges.



Weight	Order no.
kg	
2,9	89080172

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

thermoport® Plastic

Program Overview





thermoport® plastic Top loader portable - unheated / passively cooled

Unheated food transport box with lid, made of sturdy, lightweight & non-porous plastic. Hygienic double-walled & tightly welded, dishwasher-safe (up to +90°C). For stacking GN containers/thermoplates® with watertight plug-in lid, for reliable & insulated food transport. All thermoport® models, plastic & stainless steel can be stacked in combination. Passively cooled version with GN 1/1 cooling plate made of plastic integrated in the lid.

Easy to clean, dishwasher safe up to +90 °C. Max. Capacity with GN: Size 50: 11, 7L | 100: 26L



thermoport® plastic Top loader portable - heated

Heated food transport box with lid & self-regulating PTC heating fix +86°C max. +95°C, wet & dry heatable, hygienic double-walled & seal-welded. For stacking GN containers/thermoplates® with watertight plug-in lids, for reliable & insulated food transport. All thermoport® models can be stacked in combination with each other. Rated voltage 1N AC 230V 50/60Hz.

Easy to clean, dishwasher safe up to +90 °C without heating. Max. Capacity with GN: Size 50: 11, 7L | 100: 26L



thermoport® plastic Top loader portable - unheated with hybrid function

Unheated food transport box with lid & passive cold/warm area separable by Isosteg. Made of sturdy, lightweight & non-porous plastic. Hygienically double-walled & tightly welded. For space-efficient stacking of GN containers/thermoplates® with watertight plug-in lid. All thermoport® models can be stacked in combination with each other.

Separable interior in hot & cold, efficient GN stacking in various sizes/depths. Sizes/depths. Dishwasher safe up to +90 °C. Max. Max. capacity with GN: Size 100: 26L



thermoport® plastic Front loader portable - unheated

Unheated food transport box with door, made of sturdy, lightweight & non-porous plastic. Hygienically double-walled & tightly welded. For inserting GN containers/thermoplates® with watertight plug-in lid, for reliable & insulated food transport. All thermoport® models, plastic & stainless steel can be stacked in combination.

Easy to clean, dishwasher safe up to +90 °C. Max. Capacity with GN: Size 230: 26L | 500: 26L | 600: 33L | 1000: 52L | 6000: 104L

Digital HACCP documentation - safe & time-saving

Digital documentation with our CHECK HACCP system. Automatic room temperature recording in the thermoport®, via retrofittable sensors. Paper- & seamless HACCP during transport, in real time, viewable from anywhere in your dashboard.



Automatic room temp. sensor - can be retrofitted any time - order no. 94020138



thermoport® plastic Front loader portable - convection heated

Circulating-air heated food transport box with door, digital temperature setting accurate to the degree from +20°C to +85°C. Hygienic double-walled & tightly welded, dishwasher-safe without heating (up to +90°C). For inserting GN containers/thermoplates® with watertight plug-in lid. All thermoport® synthetic & stainless steel containers & stainless steel can be stacked in combination. Rated voltage 1N AC 230V 50/60Hz.

Easy cleaning, dishwasher safe up to +90 °C without heating. Max. Capacity with GN: Size 600: 33L | 1000: 52L | 6000: 104L



thermoport® plastic
Top loader portable - unheated / passively cooled



Unheated food transport box with lid, made of sturdy, lightweight & non-porous plastic. Hygienic double-walled & tightly welded, dishwasher-safe (up to +90°C). For stacking GN containers/thermoplates® with watertight plug-in lid, for reliable & insulated food transport. All thermoport® models, plastic & stainless steel can be stacked in combination. Passively cooled version with GN 1/1 cooling plate made of plastic integrated in the lid.

More info



thermoport® K 50 neutral

Max. capacity 11,7 L | Ambient temperature: -20°C to +100°C | Weight: 6,5 kg

Dimensions mm	Function	Colour	Order no.
645 x 370 x 240	neutral	orange	85020201
645 x 370 x 240	neutral	black	85020216



thermoport® K 100 unheated

Max. capacity 26 L | Ambient temperature: -20°C to +100°C | Weight: 7,5 kg

Dimensions mm	Function	Colour	Order no.
645 x 370 x 308	neutral	orange	85020301
645 x 370 x 308	neutral	black	85020328
645 x 370 x 334	passive cooled	orange	85020346
645 x 370 x 334	passive cooled	black	85020347

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

thermoport® plastic
Top loader portable - heated



Heated food transport box with lid & self-regulating PTC heating fix +86°C max. +95°C, wet & dry heatable, hygienic double-walled & seal-welded. For stacking GN containers/thermoplates® with watertight plug-in lids, for reliable & insulated food transport. All thermoport® models can be stacked in combination with each other. Rated voltage 1N AC 230V 50/60Hz.

More info

thermoport® K 50 heated

Connected load: 240 W | Plug type: Safety switch (type F) | Cable type: plain cable | Cable length: 2.000 mm | Protection class: IPX4 | Suitable for water jets (if heating element removed) | Ambient temperature: -20°C to +100°C



Dimensions mm	Capacity max. L	Weight kg	Colour	Order no.
645 x 370 x 240	12	7,5	orange	85020206
645 x 370 x 240	12	7,5	black	85020217

thermoport® K 100 heated

Connected load: 240 W | Plug type: Safety switch (type F) | Cable type: plain cable | Cable length: 2.000 mm | Protection class: IPX4 | Suitable for water jets (if heating element removed) | Ambient temperature: -20°C to +100°C



Dimensions mm	Capacity max. L	Weight kg	Colour	Order no.
645 x 370 x 308	26	8,3	orange	85020313
645 x 370 x 308	26	8,3	black	85020329

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

thermoport® plastic
Top loader portable - unheated with hybrid function



Unheated food transport box with lid & passive cold/warm area separable by Isosteg. Made of sturdy, lightweight & non-porous plastic. Hygienically double-walled & tightly welded. For space-efficient stacking of GN containers/thermoplates® with watertight plug-in lid. All thermoport® models can be stacked in combination with each other.

More info



thermoport® K 100 hybrid passive

Ambient temperature: -20°C to +100°C | Dishwasher safe up to +90 ° C

Dimensions mm	Capacity max. L	Weight kg	Colour	Order no.
700 x 425 x 368	26	7,3	orange	85020353
700 x 425 x 368	26	7,3	black	85020354

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

thermoport® plastic
Front loader portable - unheated



Unheated food transport box with door, made of sturdy, lightweight & non-porous plastic. Hygienically double-walled & tightly welded. For inserting GN containers/thermoplates® with watertight plug-in lid, for reliable & insulated food transport. All thermoport® models, plastic & stainless steel can be stacked in combination.

More info

thermoport® K Pizzaport unheated

Support distance: 83 mm | Ambient temperature: -20°C to +100°C | Dishwasher safe up to +90 ° C



Dimensions mm	Capacity max. L	Weight kg	Support rails	Colour	Order no.
397 x 394 x 340	-	4,5	2	orange	85020509

thermoport® K 600 unheated

Support distance: 36 mm | Ambient temperature: -20°C to +100°C | Dishwasher safe up to +90 ° C



Dimensions mm	Capacity max. L	Weight kg	Support rails	Colour	Order no.
610 x 435 x 385	33	8,2	7	orange	85020505
610 x 435 x 385	33	8,2	7	black	85020518

thermoport® K 1000 unheated

Support distance: 36 mm | Ambient temperature: -20°C to +100°C | Dishwasher safe up to +90 ° C



Dimensions mm	Capacity max. L	Weight kg	Support rails	Colour	Order no.
610 x 435 x 561	52	12,0	12	orange	85020401
610 x 435 x 561	52	12,0	12	black	85020412

thermoport® K 6000 unheated

Support distance: 36 mm | Ambient temperature: -20°C to +100°C | Dishwasher safe up to +90 ° C



Dimensions mm	Capacity max. L	Weight kg	Support rails	Colour	Order no.
779 x 644 x 562	104	20,5	12	orange	85020801
779 x 644 x 562	104	20,5	12	black	85020805

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

thermoport® plastic
Front loader portable - convection heated



Circulating-air heated food transport box with door, digital temperature setting accurate to the degree from +20°C to +85°C. Hygienic double-walled & tightly welded, dishwasher-safe without heating (up to +90°C). For inserting GN containers/thermoplates® with watertight plug-in lid. All thermoport® synthetic & stainless steel containers & stainless steel can be stacked in combination. Rated voltage 1N AC 230V 50/60Hz.

More info



thermoport® K 600 KB D heated

Heating control: digital | Connected load: 500 W | Plug type: Safety switch (type F) | Cable type: plain cable | Cable length: 2.000 mm | Protection class: IPX4 | Support distance: 36 mm | Ambient temperature: -20°C to +100°C

Dimensions mm	Capacity max. L	Weight kg	Support rails	Colour	Order no.
435 x 639 x 385	33	10,7	7	orange	85020526
435 x 639 x 385	33	10,7	7	black	85020527



thermoport® K 600 KB A heated

Heating control: analogue | Connected load: 500 W | Plug type: Safety switch (type F) | Cable type: plain cable | Cable length: 2.000 mm | Protection class: IPX4 | Support distance: 36 mm | Ambient temperature: -20°C to +100°C

Dimensions mm	Capacity max. L	Weight kg	Support rails	Colour	Order no.
435 x 639 x 385	33	10,7	7	orange	85020524
435 x 639 x 385	33	10,7	7	black	85020525



thermoport® K 1000 circul.heated

Heating control: digital | Connected load: 810 W | Plug type: Safety switch (type F) | Cable type: plain cable | Cable length: 2.000 mm | Protection class: IPX4 | Support distance: 36 mm | Ambient temperature: -20°C to +100°C

Dimensions mm	Capacity max. L	Weight kg	Support rails	Colour	Order no.
688 x 435 x 561	52	17,6	12	orange	85020423
688 x 435 x 561	52	17,6	12	black	85020424



thermoport® K 1000 KB D heated

Heating control: digital | Connected load: 500 W | Plug type: Safety switch (type F) | Cable type: plain cable | Cable length: 2.000 mm | Protection class: IPX5 | Support distance: 36 mm | Ambient temperature: -20°C to +100°C

Dimensions mm	Capacity max. L	Weight kg	Support rails	Colour	Order no.
435 x 634 x 561	52	14,8	12	orange	85020436
435 x 634 x 561	52	14,8	12	black	85020437

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

thermoport® K 1000 KB A heated

Heating control: analogue | Connected load: 500 W | Plug type: Safety switch (type F) | Cable type: plain cable | Cable length: 2.000 mm | Protection class: IPX4 | Support distance: 36 mm | Ambient temperature: -20°C to +100°C



Dimensions mm	Capacity max. L	Weight kg	Support rails	Colour	Order no.
435 x 634 x 561	52	14,8	12	orange	85020434
435 x 634 x 561	52	14,8	12	black	85020435

thermoport® K 6000 KB D heated

Heating control: digital | Connected load: 500 W | Plug type: Safety switch (type F) | Cable type: plain cable | Cable length: 2.000 mm | Protection class: IPX4 | Support distance: 36 mm | Ambient temperature: -20°C to +100°C



Dimensions mm	Capacity max. L	Weight kg	Support rails	Colour	Order no.
644 x 779 x 562	104	23,0	12	orange	85020815
644 x 779 x 562	104	23,0	12	black	85020816

thermoport® K 6000 KB A heated

Heating control: analogue | Connected load: 500 W | Plug type: Safety switch (type F) | Cable type: plain cable | Cable length: 2.000 mm | Protection class: IPX4 | Support distance: 36 mm | Ambient temperature: -20°C to +100°C



Dimensions mm	Capacity max. L	Weight kg	Support rails	Colour	Order no.
644 x 779 x 562	104	23,0	12	orange	85020813
644 x 779 x 562	104	23,0	12	black	85020814

Made in Germany

thermoport® plastic Accessories

Matching accessories for all thermoport® plastic models - such as slide-in frames for various smaller GN container sizes, synthetic GN cooling or heating pellets for passive cold / warm holding, through to the chassis and rolliport for non-slip transport of all thermoport® models.

More info



Insert frame - 1/6, 1/9

Stainless steel GN 1/1 insert frame with 2 cross supports - for the insertion of smaller GN sizes, such as 6x 1/6 or 9x 1/9.

Weight kg	Order no.
0,7	85012010



Insert frame - 1/4, 1/6, 2/4

Stainless steel GN 1/1 insert frame with 1 longitudinal supports - for the insertion of smaller GN sizes, such as 4x 1/4, 6x 1/6 or 2x 2/4.

Weight kg	Order no.
0,5	85012009



Sub-frame - thermoport® plastic

Stainless steel mobile frame with 4 corner bumpers, 2 swivel castors with brakes and 2 fixed castors for the transport of portable plastic thermoport® models.


Weight kg	Order no.
5,2	88140106



Mobile frame - thermoport®K 1000

Mobile frame with a stainless steel plate and stainless steel castors for fixed mounting on the thermoport® K 1000.

Weight kg	Order no.
6,3	88140105



GN bridge piece - thermoport® 50K/100K

Cross support without a spring for dividing thermoport® 50/100K - to accommodate smaller GN sizes.

Weight kg	Order no.
0,1	84190202

Made in Germany

ISO divider 1/1 - TH K 1000 - black

Plastic insulated divider in a GN size for the insulated separation of a cold and hot zone - when transporting food in the thermoport® K 1000.

Weight kg	Order no.
1,1	85022069

Insulated divider plastic - orange

Plastic insulated divider - for the thermal separation of a cold and hot zone in plastic thermo-ports.

Weight kg	Order no.
1,1	85022012

Iso divider - thermoport® K 100.

Plastic insulated drawer for the insulated separation of a cold and hot zone - when transporting food in the thermoport® K 100.

Weight kg	Order no.
1,6	85022042

Trolley - thermoport® K 6000

Suitable transport trolley for the plastic thermoport® 6000.



Weight kg	Order no.
11,3	88140201

Rolliport plastic - thermoport® K

The universal transport trolley for all portable thermoport® models without castors.



Weight kg	Order no.
8,6	88070601

Stacking catch - thermoport® K 1000

Stack locking mechanism for mounting on the base of the plastic thermoport® 1000 - for the safe and non-slip stacking of boxes.



Weight kg	Order no.
1,0	85022061

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

Plug for heating TP 50KB/100KB

Weight kg	Order no.
0,0	37130841



GN cooling pellet 1/1 plastic - black

Plastic GN 1/1 cooling plate for pre-heating and passive cooling during the transportation of food in Rieber thermoport® models, can be inserted horizontally on the support rails.

Weight kg	Order no.
2,7	85022067



GN cooling pellet plastic 1/1 - orange

Plastic GN 1/1 cooling plate for pre-heating and passive cooling during the transportation of food in Rieber thermoport® models, can be inserted horizontally on the support rails.

Weight kg	Order no.
2,6	85022038



Heating pellet CNS GN 1/1

The stainless steel heating plate {514} for pre-tempering and passive keeping warm via the food transport in Rieber thermoport® models can be inserted horizontally via the support ledges.

Weight kg	Order no.
2,9	89080172



Heating pellet CNS GN 1/2 - asymmetrical

The stainless steel heating plate GN 1/2 for pre-tempering and passive keeping warm via the food transport in Rieber thermoport® models can be inserted horizontally via the support ledges.

Weight kg	Order no.
1,4	89080171

Transport / dispensing trolley for portable plastic & stainless steel thermoport® models



Robust stainless steel trolley, for transporting portable thermoport® plastic/ stainless steel boxes 50, 100, 600 or 1000. On sturdy shelf with non-slip embossing for 1-3 thermoport® boxes. Can also be used for mobile food serving, by direct scooping from thermoport® top-loading models. All-round impact protection, practical additional storage space on the lower shelf.

More info

Transp./serv.trolley 3 x thermoport®

2fixed-; 1 siwvel-; 1 swivel castors with brakes | Castor Ø: 125 mm | 4 corner bumpers



Dimensions mm	Weight kg	Max. loading capacity kg	Order no.
1775 x 706 x 840	28,0	210	88150301

Transp./serv.trolley 2 x thermoport®

2fixed-; 1 siwvel-; 1 swivel castors with brakes | Castor Ø: 125 mm | 4 corner bumpers



Dimensions mm	Weight kg	Max. loading capacity kg	Order no.
1271 x 706 x 840	22,0	130	88150201

Transp./serv.trolley 1 x thermoport®

2fixed-; 1 siwvel-; 1 swivel castors with brakes | Castor Ø: 125 mm | 4 corner bumpers



Dimensions mm	Weight kg	Max. loading capacity kg	Order no.
706 x 705 x 840	13,5	80	88150101

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

Single portion thermo-port® plastic

Program Overview





thermoport® 10 - plastic for 1 x menu with soup

Unheated insulation box, double-walled & tightly welded, dishwasher-safe up to +90 °C. Set with 1x 3-piece food tray latent heat storage, 1/6 32mm side dish, each incl. matching lid. For safe transport & keeping single-serving meals warm/cold. Models of 10 (10, 10D, 10KW) are standardised & the food/side dish trays can be used in a compatible way.

Simple embossing in the lid - for 1 x menu (3 or 1 part) with soup. Dishwasher safe up to +90 °C



thermoport® 10 D - plastic for 1 x menu and 2 x side dishes

Unheated insulation box, double-walled & tightly welded, dishwasher-safe up to +90 °C. Set with 1x 3-piece food tray latent heat storage, 2x 1/6 32mm side dish, each incl. matching lid. For safe transport & keeping single-serving meals warm/cold. Models of 10 (10, 10D, 10KW) are standardised & the food/ supplement trays can be used in a compatible way.

Double embossing in the lid - for 1 x menu (3- or 1-part) and 2 x side dishes. Dishwasher safe up to +90 °C



thermoport® 10 KW - plastic with cold comp. & w/o cooling pellet - for food, side dish & cold dish

solation box with extra cold compartment, double-walled & tightly welded, dishwasher-safe up to +90 °C. Set equipment: 1x 3-piece food tray latent heat sp., 1x 1/6 22mm & 2x 1/9 22mm side dish tray, each incl. matching lid & 1x 1/6 cooling pellet. For transporting cold/hot meals. Models of 10 (10, 10D, 10KW) are standardised & the food/supplement trays can be used in a compatible way.

Additional separate cold compartment in the lid on top - for 1 x meal and 1 x cold dish (dessert/salad) with matching food trays. Dishwasher-safe up to +90 °C



thermoport® 20 - Plastic

Unheated insulation box, completely equipped with porcelain system dishes:
1x square menu bowl + heat pellet, 1x round soup bowl and 2x square side dish, each incl. matching plastic lid. Double-walled & tightly welded, dishwasher-safe up to +90°C. Weight loaded approx. 5 kg


With porcelain system dishes: 1x square menu bowl + heat pellet, 1x round soup bowl & 2x square side dishes, each + lid. Dishwasher safe up to +90°C

Digital HACCP documentation - safe & time-saving

Digital HACCP documentation with the CHECK HACCP system. App temperature measurement with Bluetooth-capable core temperature sensor. From goods receipt, production to output. Paper & complete HACCP in real time, visible everywhere in your dashboard.



Core temperature sensor - can be retrofitted at any time - order no. 94 01 01 05



thermoport® 21 - plastic with menu plate 1 or 2 pcs, heat pellet, 1x soup, 2x side dish

Unheated insulation box, completely equipped with porcelain system dishes: 1x round plate 1tlg (Ø230mm) + heat pellet, 1x round soup bowl and 2x square side dishes (small&large), each incl. matching plastic lid. Double-walled & tightly welded, dishwasher-safe up to +90°C. Weight when loaded approx. 5 kg.

With porcelain system dishes: 1x round plate 1tlg (Ø230mm) + heat pellet, 1x round soup bowl & 2x square side dishes, each with lid. Dishwasher safe up to +90°C



thermoport® 10 - plastic for 1 x menu with soup



Unheated insulation box, double-walled & tightly welded, dishwasher-safe up to +90 °C. Set with 1x 3-piece food tray latent heat storage, 1/6 32mm side dish, each incl. matching lid. For safe transport & keeping single-serving meals warm/cold. Models of 10 (10, 10D, 10KW) are standardised & the food/side dish trays can be used in a compatible way.

More info



thermoport® K 10

Unheated single-portion insulation box made of plastic with a single recess in the lid, double-walled and tightly welded, dishwasher-safe (up to +90°C) - for the transport of 1 x meal and soup through „meals on wheels“.

Dimensions mm	Weight kg	Colour	Order no.
380 x 220 x 153	1,3	orange	85020101



thermoport® 10 set 1

Set consisting of 1x unheated plastic single-portion insulation box + lid, 1x 3-compartment, stainless steel food tray + lid, 1x GN 1/6 side dish tray, 32 mm deep + press-in lid.

Dimensions mm	Weight kg	Colour	Order no.
380 x 220 x 153	3,2	orange	85022705

Made in Germany

thermoport® 10 D - plastic for 1 x menu and 2 x side dishes



Unheated insulation box, double-walled & tightly welded, dishwasher-safe up to +90 °C. Set with 1x 3-piece food tray latent heat storage, 2x 1/6 32mm side dish, each incl. matching lid. For safe transport & keeping single-serving meals warm/cold. Models of 10 (10, 10D, 10KW) are standardised & the food/supplement trays can be used in a compatible way.

More info

thermoport® K 10 D

Unheated single-portion insulation box made of plastic with a double recess in the lid, double-walled and tightly welded, dishwasher-safe (up to +90°C) - for the transport of 1 x meal and 2 side dishes through „meals on wheels“.



Dimensions mm	Weight kg	Colour	Order no.
377 x 221 x 158	1,2	orange	85020102

thermoport® 10 D set 1

Set consisting of 1x unheated plastic single-portion insulation box with a double recess in the lid + lid, 1x 3-compartment, stainless steel food tray + lid, 2x GN 1/6 side dish tray, 32 mm deep + press-in lid.



Dimensions mm	Weight kg	Colour	Order no.
380 x 220 x 153	3,4	orange	85022706

Made in Germany

Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

thermoport® 10 KW - plastic with cold comp. & w/o cooling pellet - for food, side dish & cold dish



solation box with extra cold compartment, double-walled & tightly welded, dishwasher-safe up to +90 °C. Set equipment: 1x 3-piece food tray latent heat sp., 1x 1/6 22mm & 2x 1/9 22mm side dish tray, each incl. matching lid & 1x 1/6 cooling pellet. For transporting cold/hot meals. Models of 10 (10, 10D, 10KW) are standardised & the food/supplement trays can be used in a compatible way.

More info



thermoport® K 10 KW - orange

Unheated single-portion insulation box made of plastic with an additional cold compartment, double-walled and tightly welded, dishwasher-safe (up to +90°C) - for the transport of 1 x meal and 1 cold dish with suitable food trays through „meals on wheels“.

Dimensions mm	Weight kg	Order no.
380 x 220 x 165	1,5	85020103



thermoport® 10 KW set 1

Set consisting of 1x unheated plastic single-portion insulation box with a cold compartment + intermediate compartment and lid, 1x 3-compartment, stainless steel food tray + lid, 2x GN 1/6 side dish tray, 32 mm deep + press-in lid.

Dimensions mm	Weight kg	Order no.
380 x 220 x 165	3,7	85022702



thermoport® 10 KW set 2

Set with a cooling pellet consisting of 1x unheated plastic single-portion insulation box with a cold compartment + intermediate compartment and lid, 1x 3-compartment, stainless steel food tray + lid, 1x GN 1/6 side dish tray, 32 mm deep + press-in lid, 1x cooling pellet, 2x GN1/9 side dish tray, 22 mm.

Dimensions mm	Weight kg	Order no.
380 x 220 x 165	4,2	85022703



thermoport® 10 KW set 3

Set consisting of 1x unheated plastic single-portion insulation box with a cold compartment + intermediate compartment and lid, 1x 3-compartment, stainless steel food tray + lid, 1x GN 1/6 side dish tray, 32 mm deep + press-in lid and 2x GN1/9 side dish tray, 22 mm.

Dimensions mm	Weight kg	Order no.
380 x 220 x 165	3,8	85022704

Made in Germany

thermoport® 20 - Plastic



Unheated insulation box, completely equipped with porcelain system dishes: 1x square menu bowl + heat pellet, 1x round soup bowl and 2x square side dish, each incl. matching plastic lid. Double-walled & tightly welded, dishwasher-safe up to +90°C. Weight loaded approx. 5 kg

More info

thermoport® K 20 with handle variant S4

Unheated single-serving isolation box made of plastic equipped with system dishes, double-walled and tightly welded, dishwasher safe (up to +90 °C) - for „meals on wheels“ transport. Set includes 1 x 3-fluted CNS menu tray with latent heat storage, 1 x porcelain soup bowl, 2 x porcelain cold bowls.



Dimensions mm	Weight kg	Order no.
454 x 364 x 111	5,2	85020704

thermoport® K 20 neutral V. P3.1-orange

Unheated single-portion insulation box made of plastic, equipped with systemware, double-walled and tightly welded, dishwasher-safe (up to +90°C) - for the transport of „meals on wheels“. Set contains 1 x heating pellet and 1 x undivided meal tray, 1 x soup bowl and 2 x cold food trays, each made of porcelain.



Dimensions mm	Weight kg	Order no.
454 x 364 x 111	4,5	85020716

thermoport® K 20 neutral V. P3.2-orange

Unheated single-portion insulation box made of plastic, equipped with systemware, double-walled and tightly welded, dishwasher-safe (up to +90°C) - for the transport of „meals on wheels“. Set contains 1 x heating pellet and 1 x 3-compartment meal tray, 1 x soup bowl and 2 x cold food trays, each made of porcelain.



Dimensions mm	Weight kg	Order no.
454 x 364 x 111	4,3	85020717

thermoport® K 20 unheated unload.-orange

Unheated single-portion insulation box made of plastic, without any equipment, double-walled and tightly welded, dishwasher-safe (up to +90°C) - for the transport of „meals on wheels“.




Dimensions mm	Weight kg	Order no.
454 x 364 x 111	2,0	85020705

Made in Germany


Our General Conditions of Sale and Delivery apply. We reserve the right to make technical changes. Valid from 01/01/2023.

thermoport® 21 - plastic with menu plate 1 or 2 pcs, heat pellet, 1x soup, 2x side dish



Unheated insulation box, completely equipped with porcelain system dishes: 1x round plate 1tlg (Ø230mm) + heat pellet, 1x round soup bowl and 2x square side dishes (small&large), each incl. matching plastic lid. Double-walled & tightly welded, dishwasher-safe up to +90°C. Weight when loaded approx. 5 kg.


More info



thermoport® K 21 unheated V.1.1 - grey

Unheated single-portion insulation box made of plastic, equipped with systemware, double-walled and tightly welded, dishwasher-safe (up to +90°C) - for the transport of 1 x meal on an undivided plate, 1x soup and 2x side dishes through „meals on wheels“.

Dimensions mm	Weight kg	Order no.
454 x 364 x 111	4,5	85020711



thermoport® K 21 unheated V.1.2 - grey

Unheated single-portion insulation box made of plastic, equipped with systemware, double-walled and tightly welded, dishwasher-safe (up to +90°C) - for the transport of 1 x meal on an undivided plate, 1x soup and 2x side dishes through „meals on wheels“.

Dimensions mm	Weight kg	Order no.
454 x 364 x 111	3,9	85020712

Made in Germany